

Specifications



Photo is representative



Eaton 278766

Eaton Moeller series xEffect - FAZ MCB. FAZ, 2-pole, tripping characteristic: C, rated current In: 63 A

General specifications

PRODUCT NAME	Eaton Moeller series xEffect - FAZ MCB
CATALOG NUMBER	278766
MODEL CODE	FAZ-C63/2
EAN	4015082787660
PRODUCT LENGTH/DEPTH	80 mm
PRODUCT HEIGHT	75.5 mm
PRODUCT WIDTH	36 mm
PRODUCT WEIGHT	0.246 kg
COMPLIANCES	RoHS conform
CERTIFICATIONS	IEC/EN 60947-2 IEC/EN 60898 EN45545-2 IEC 61373
CATALOG NOTES	C CURVE



Powering Business Worldwide

Additional information

CURRENT LIMITING CLASS

3

FEATURES

Additional equipment possible

SPECIAL FEATURES

Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity

USED WITH

Miniature circuit breaker FAZ

Delivery programme

AMPERAGE RATING

63 A

APPLICATION

- Switchgear for industrial and advanced commercial applications
- xEffect - Switchgear for industrial and advanced commercial applications

NUMBER OF POLES

Two-pole

NUMBER OF POLES (PROTECTED)

2

NUMBER OF POLES (TOTAL)

2

RELEASE CHARACTERISTIC

C

TRIPPING CHARACTERISTIC

C

TYPE

- FAZ
- Miniature circuit breaker

Design verification to IEC/EN 61439

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION	Does not apply, since the

Design verification to IEC/EN 61439 - technical data

AMBIENT OPERATING TEMPERATURE - MAX	75 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT	11.5 W
HEAT DISSIPATION CAPACITY	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	63 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT	0 W

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.

Technical data - electrical

ADMISSIBLE BACK-UP FUSE - MAX	125 A gL/gG
BREAKING CAPACITY	5 kA (UL1077)
DIRECTION OF INCOMING SUPPLY	As required
FREQUENCY RATING - MAX	60 Hz
FREQUENCY RATING - MIN	50 Hz
LIFESPAN, ELECTRICAL	10000 operations
OPERATIONAL SWITCHING CAPACITY	7.5 kA
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	2
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4 kV
RATED INSULATION VOLTAGE (UI)	440 V
RATED OPERATIONAL VOLTAGE (UE) - MAX	400 V
RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC/EN 60898-1) - ICN AT 230 V	10 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC/EN 60898-1)- ICN AT 400 V	10 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2)- ICU AT 230 V	15 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2)- ICU AT 400 V	15 kA
RATED SWITCHING CAPACITY (IEC/EN 60947-2)	15 kA
SELECTIVITY CLASS	3
VOLTAGE RATING	240 V AC / 415 V AC
VOLTAGE RATING (UL)	480Y/277 V
VOLTAGE RATING AT DC	60 V DC (per pole)
VOLTAGE TYPE	AC

Technical data - mechanical

BUILT-IN DEPTH	70.5 mm
BUSBAR MATERIAL THICKNESS	0.8 mm - 2 mm
CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MAX	25 mm ²
CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MIN	1 mm ²
CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MAX	25 mm ²
CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MIN	1 mm ²
DEGREE OF PROTECTION	IP20 IP40 (when fitted)
ENCLOSURE WIDTH	80 mm
FRAME	45 mm
MOUNTING METHOD	Top-hat rail IEC/EN 60715
MOUNTING POSITION	As required
MOUNTING WIDTH	17.5 mm
MOUNTING WIDTH PER POLE	17.5 mm
TERMINAL CAPACITY (CONTROL CABLE)	25 mm ² (1x)
TERMINAL CAPACITY OF SCREW TERMINALS FOR MAIN CABLE	10 mm ² (2x)
TERMINAL PROTECTION	Finger and hand touch safe, DGUV VS3, EN 50274
TERMINALS (TOP AND BOTTOM)	Twin-purpose terminals
WIDTH IN NUMBER OF MODULAR SPACINGS	2

Resources

CATALOGUES	eaton-xeffect-industrial-switchgear-range-catalog-ca003002en-en-us.pdf
CHARACTERISTIC CURVE	eaton-mcb-tripping-characteristic-xeffect-faz-characteristic-curve-002.eps eaton-mcb-xeffect-faz-characteristic-curve.eps eaton-mcb-current-xeffect-faz-characteristic-curve.eps eaton-mcb-xeffect-faz-characteristic-curve-002.eps eaton-xeffect-faz-mcb-characteristic-curve.jpg eaton-mcb-current-xeffect-faz-characteristic-curve-002.eps
DECLARATIONS OF CONFORMITY	eaton-mcb-declaration-of-conformity-eu250395en.pdf eaton-mcb-declaration-of-conformity-uk251436en.pdf
DRAWINGS	eaton-mcb-xeffect-faz-dimensions-002.eps eaton-xeffect-faz-mcb-dimensions-002.jpg eaton-mcb-faz-xeffect-faz-3d-drawing-002.eps eaton-xeffect-faz-mcb-3d-drawing-009.jpg eaton-xeffect-faz-mcb-3d-drawing-010.jpg eaton-xeffect-faz-mcb-3d-drawing-002.jpg
ECAD MODEL	ETN.FAZ-C63_2
INSTALLATION INSTRUCTIONS	eaton-mcb-rcb-rcbo-g9-il019140zu.pdf
MCAD MODEL	eaton-non-selective-universal-mcb-mcad-3d-models-faz-xxx-2p.stp eaton-non-selective-universal-mcb-mcad-drawings-faz-xxx-2p.dwg

PEP ECO-PASSPORT	eaton-non-selective-universal-mcb-pep-eato-00047-v0101-en.pdf
WIRING DIAGRAMS	eaton-mcb-xeffect-faz-wiring-diagram-002.eps eaton-xpole-mmc4-6-m-mcb-wiring-diagram-003.jpg

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

