

Specifications



Photo is representative

Eaton 281668

Eaton Moeller series NZM - Molded Case Circuit Breaker. Connection, on rear, 13mm, 3p

General specifications

PRODUCT NAME	Eaton Moeller series NZM multi-function device adapter
CATALOG NUMBER	281668
MODEL CODE	NZM3-XKR13
EAN	4015082816681
PRODUCT LENGTH/DEPTH	140 mm
PRODUCT HEIGHT	30 mm
PRODUCT WIDTH	110 mm
PRODUCT WEIGHT	0.234 kg
COMPLIANCES	UL/CSA IEC RoHS conform
CERTIFICATIONS	IEC60947-2 UL (File No. E31593) CSA (File No. 22086) UL listed UL489 CE marking CSA-C22.2 No. 5-09 CSA (Class No. 1432-01) UL (Category Control Number DIVQ) Specially designed for North America CSA certified



Powering Business Worldwide

Additional information

MODEL	Other
--------------	-------

Delivery programme

AMPERAGE RATING	630 A
------------------------	-------

FRAME	NZM3
--------------	------

NUMBER OF POLES	Three-pole
------------------------	------------

SPECIAL FEATURES	• Current limiting circuit breaker • For NZM3 component adapter
-------------------------	---

SUITABLE FOR	Three-pole
---------------------	------------

TYPE	• Accessory • Multifunction component adapter • Connection block for component adapter • 60 mm system
-------------	---

USED WITH	PN3 Feeder circuits, branch circuits NZM3 N(S)3
------------------	--

Design verification to IEC/EN 61439

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION	Does not apply, since the

Technical data - electrical

AMPERAGE RATING	630 A
VOLTAGE RATING (UL CSA 13)	Max. 480 Y / 277 V

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.

Technical data - mechanical

DEGREE OF PROTECTION	IP20
SPECIAL FEATURES	• Current limiting circuit breaker • For NZM3 component adapter

Resources

BROCHURES	eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf eaton-digital-nzm-brochure-br013003en-en-us.pdf
CATALOGUES	eaton-digital-nzm-catalog-ca013003en-en-us.pdf eaton-circuit-breaker-connection-nzm-rear-connection-dimensions-002.eps
DRAWINGS	eaton-circuit-breaker-connection-nzm-rear-connection-dimensions-005.eps eaton-circuit-breaker-connection-nzm-connection-block-3d-drawing.eps
INSTALLATION INSTRUCTIONS	eaton-circuit-breakers-nzm3-xkr-o-u-g-connection-il01219048z.pdf
INSTALLATION VIDEOS	The new digital NZM Range Introduction of the new digital circuit breaker NZM
MCAD MODEL	DA-CS-nzm3_xkr13_o_u

[eaton-mccb-terminals-mcad-drawings-nzm3-xkr13-o-u.dwg](#)

TECHNICAL DATA SHEETS

[eaton-nzm-technical-information-sheet](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

