

Specifications



Eaton 288894

Eaton XIOC Empty module for XC100/200 to cover free slots

General specifications

PRODUCT NAME	Eaton XIOC Accessory Plug
CATALOG NUMBER	288894
MODEL CODE	XIOC-NOP
EAN	4015082888947
PRODUCT LENGTH/DEPTH	100 mm
PRODUCT HEIGHT	95 mm
PRODUCT WIDTH	30 mm
PRODUCT WEIGHT	0.085 kg

CERTIFICATIONS	UL508 CSA Class No.: 2252-01 UL Category Control No.: NRAQ CSA-C22.2 No. 0-M CSA CE CSA File No.: 012528 UL File No.: E135462 CSA-C22.2 No. 142-M UL
-----------------------	---



Powering Business Worldwide

Climatic environmental conditions

**AMBIENT OPERATING
TEMPERATURE - MAX** 55 °C

**AMBIENT OPERATING
TEMPERATURE - MIN** 0 °C

Design verification

10.10 TEMPERATURE RISE The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

**10.11 SHORT-CIRCUIT
RATING** Is the panel builder's responsibility.

**10.12 ELECTROMAGNETIC
COMPATIBILITY** Is the panel builder's responsibility.

**10.13 MECHANICAL
FUNCTION** The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

**10.2.2 CORROSION
RESISTANCE** Meets the product standard's requirements.

**10.2.3.1 VERIFICATION OF
THERMAL STABILITY OF
ENCLOSURES** Meets the product standard's requirements.

**10.2.3.2 VERIFICATION OF
RESISTANCE OF
INSULATING MATERIALS
TO NORMAL HEAT** Meets the product standard's requirements.

**10.2.3.3 RESIST. OF
INSUL. MAT. TO
ABNORMAL HEAT/FIRE
BY INTERNAL ELECT.
EFFECTS** Meets the product standard's requirements.

**10.2.4 RESISTANCE TO
ULTRA-VIOLET (UV)
RADIATION** Meets the product standard's requirements.

10.2.5 LIFTING Does not apply, since the entire switchgear needs to be evaluated.

**10.2.6 MECHANICAL
IMPACT** Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 INSCRIPTIONS Meets the product standard's requirements.

**10.3 DEGREE OF
PROTECTION OF
ASSEMBLIES** Meets the product standard's requirements.

**10.4 CLEARANCES AND
CREEPAGE DISTANCES** Meets the product standard's requirements.

**10.5 PROTECTION
AGAINST ELECTRIC
SHOCK** Does not apply, since the entire switchgear needs to be evaluated.

**10.6 INCORPORATION OF
SWITCHING DEVICES AND
COMPONENTS** Does not apply, since the entire switchgear needs to be evaluated.

10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W

General information

DEGREE OF PROTECTION IP20

Resources

	eaton-xc300-modular-plc-brochure-br050008en-en-us.pdf
BROCHURES	Slice card modular I/O system for the machine building industry XN300 - brochure
ECAD MODEL	DA-CE-ETN.XIOC-NOP
MCAD MODEL	eaton-accessories-mcad-drawings-xioc-leer.dwg DA-CS-xioc_leer

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

