

Specifications



Eaton 289195

Eaton Moeller® series M22 Joystick, with one operating point per operating direction, With plastic shaft, 2 positions, Bezel: titanium, momentary, Horizontal

General specifications

PRODUCT NAME	Eaton Moeller® series M22 joystick
CATALOG NUMBER	289195
MODEL CODE	M22-WJ2H
EAN	4015082891954
PRODUCT LENGTH/DEPTH	100 mm
PRODUCT HEIGHT	30 mm
PRODUCT WIDTH	30 mm
PRODUCT WEIGHT	0.028 kg
COMPLIANCES	CE Marked
CERTIFICATIONS	EN 60947-5 CSA Std. C22.2 No. 14-05 UL 508 IEC 60947-5 CSA Std. C22.2 No. 94-91 VDE CE IEC/EN 60947 VDE 0660 UL CSA File No.: 012528 UL Category Control No.: NKCR CSA-C22.2 No. 14-05 IEC/EN 60947-5 UL File No.: E29184 CSA-C22.2 No. 94-91 CSA CSA Class No.: 3211-03



Powering Business Worldwide

Actuator

ACTUATING FORCE	5 N
ACTUATOR FUNCTION	Horizontal Momentary
BEZEL COLOR	Titanium
BEZEL MATERIAL	Plastic
FITTED WITH:	Plastic shaft Retraction in 0-position Filament bulb (24 V) Front ring
NUMBER OF ACTUATION DIRECTIONS	2

Communication

CONNECTION TO SMARTWIRE-DT	Yes With SWD-RMQ connections
-----------------------------------	---------------------------------

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Design verification

10.10 TEMPERATURE RISE	Not applicable.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W

General information

ACCESSORIES	Plastic shaft
DEGREE OF PROTECTION	IP66 NEMA 4X, 13
LIFESPAN, MECHANICAL	100,000 Operations
MOUNTING POSITION	As required
OPENING DIAMETER	22.5 mm
OPERATING FREQUENCY	2000 Operations/h
PRODUCT CATEGORY	RMQ-Titan
TYPE	Joystick

Resources

CATALOGUES

[eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf](#)

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

DECLARATIONS OF CONFORMITY

[eaton-key-operated-actuator-declaration-of-conformity-eu251544en.pdf](#)

[eaton-operating-m22-joystick-dimensions.eps](#)

[eaton-operating-operating-m22-joystick-dimensions.eps](#)

DRAWINGS

[eaton-general-m22-symbol.eps](#)

[eaton-general-m22-standards.eps](#)

[eaton-operating-symbol-m22-joystick-symbol.eps](#)

[eaton-general-approval-m22-symbol.eps](#)

ECAD MODEL

[ETN.289195.edz](#)

INSTALLATION INSTRUCTIONS

[IL04716002Z](#)

MCAD MODEL

[eaton-toggles-joysticks-mcad-drawings-joystick-2-fach.dwg](#)

[DA-CS-joystick 2 fach](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

