

Specifications



Photo is representative

Eaton 290173

Eaton Moeller® series LS Position switch, Roller lever, Complete unit, 1 N/O, 1 NC, Cage Clamp, Yellow, Insulated material, -25 - +70 °C, Short

General specifications

PRODUCT NAME	Eaton Moeller® series LS Position switch
CATALOG NUMBER	290173
MODEL CODE	LS-11/LS
EAN	4015082901738
PRODUCT LENGTH/DEPTH	33.5 mm
PRODUCT HEIGHT	91 mm
PRODUCT WIDTH	31 mm
PRODUCT WEIGHT	0.06 kg
COMPLIANCES	CE Marked
CERTIFICATIONS	IEC 60947-5 EN 60947-5 CSA Std. C22.2 No. 14 UL 508 CSA-C22.2 No. 14 IEC/EN 60947 IEC/EN 60947-5 CSA Class No.: 3211-03 CSA File No.: 012528 CE CSA UL UL Category Control No.: NKCR UL File No.: E29184

CATALOG NOTES

- The operating head can be rotated 90° to enable adaptation to the specified approach direction
- Using the product in areas exposed to ozone and UV radiation or in sub-zero temperatures



Powering Business Worldwide

in unprotected outdoor environments (e.g. altitudes above 1,000 m, unprotected sunlight) may reduce the degree of protection. The customer / user must validate the overall application accordingly. If applicable, the use of the LS-...-CC (Cold Climate) variants should be considered.

Actuator

ACTUATING FORCE AT BEGINNING/END OF STROKE 1.0 N/8.0 N

ACTUATING TORQUE OF ROTARY DRIVES 0.2 Nm

ACTUATOR TYPE Roller lever

OPERATING SPEED Max. 1 m/s (with DIN cam, mechanical actuation)
For angle of actuation $\alpha = 30^\circ/45^\circ$

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX 70 °C

AMBIENT OPERATING TEMPERATURE - MIN -25 °C

CLIMATIC PROOFING Damp heat, cyclic, to IEC 60068-2-30
Damp heat, constant, to IEC 60068-2-78

Ambient conditions, mechanical

MOUNTING POSITION As required

SHOCK RESISTANCE 25 g, Standard-action contact, Mechanical, Half-sinusoidal shock 20 ms

Contacts

CONTROL CIRCUIT RELIABILITY 1 failure per 10,000,000 switching operations (Statistically determined, at 24 V DC/5 mA)
1 failure per 5,000,000 switching operations (statistically determined, at 5 V DC/1 mA)

NUMBER OF CONTACTS (CHANGE-OVER CONTACTS) 0

NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS) 1

NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS) 1

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION	Does not apply, since the

Electrical rating

RATED INSULATION VOLTAGE (UI)	400 V
RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V	6 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 24 V	6 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V	4 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 110 V	0.6 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 125 V	0.8 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 220 V, 230 V	0.3 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 24 V	3 A
SHORT-CIRCUIT PROTECTION RATING	Max. 6 A gG/gL, Fuse, Contacts
SUPPLY FREQUENCY	Max. 400 Hz, Contacts
RATED CONDITIONAL SHORT-CIRCUIT CURRENT (IQ)	1 kA

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0.17 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	6 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W

Features & functions	
ELECTRIC CONNECTION TYPE	Cable entry metrical
ENCLOSURE COLOR	Yellow Cover
ENCLOSURE MATERIAL	Insulated material Plastic
FEATURES	Positive opening Forced opening
SWITCH FUNCTION TYPE	Slow-action switch

General information	
CONNECTION TYPE	Cage Clamp
DEGREE OF PROTECTION	IP66/IP67 NEMA Other
LIFESPAN	8,000,000 mechanical Operations
OPERATING FREQUENCY	6000 Operations/h
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Roller lever
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4000 V AC
REPETITION ACCURACY	0.15 mm (Contacts/switching)

	capacity)
SUITABLE FOR	Safety functions
TYPE	Safety position switch

Safety	
EXPLOSION SAFETY CATEGORY FOR DUST	None
EXPLOSION SAFETY CATEGORY FOR GAS	None

Terminal capacities	
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	1 x (0.5 - 1.5) mm ²
TERMINAL CAPACITY (SOLID)	1 x (0.5 - 2.5) mm ²

Resources

	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
CATALOGUES	eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf
CONTROL TRAVEL DIAGRAM	eaton-position-switches-diagram-ls-contact-travel-diagram-002.eps
DECLARATIONS OF CONFORMITY	eaton-position-switch-declaration-of-conformity-eu251556en.pdf eaton-position-switch-declaration-of-conformity-uk251032en.pdf
DRAWINGS	eaton-position-switches-ls-dimensions-003.eps eaton-position-switches-plunger-ls-dimensions-004.eps eaton-position-switches-ls-dimensions-006.eps eaton-operating-button-symbol-008.eps
ECAD MODEL	ETN.290173.edz
INSTALLATION INSTRUCTIONS	IL053001ZU
MCAD MODEL	eaton-mechanical-limit-switches-mcad-drawings-ls-ls.dwg DA-CS-ls_ls
SALES NOTES	eaton-safety-switches-rs-titan-flyer-fl053001en-en-us.pdf
WIRING DIAGRAMS	eaton-position-switches-contact-ls-wiring-diagram.eps

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

