

Specifications



Eaton 292443

Eaton xEnergy Basic LV systems Low voltage switchgear. Sheet steel door with rotary door handle HxW=1200x600mm, white

General specifications

PRODUCT NAME	Eaton xEnergy Basic door
CATALOG NUMBER	292443
MODEL CODE	BP-DS-600/12-W
EAN	4015082924430
PRODUCT LENGTH/DEPTH	38 mm
PRODUCT HEIGHT	1200 mm
PRODUCT WIDTH	600 mm
PRODUCT WEIGHT	6.7 kg
COMPLIANCES	RoHS conform



Powering Business Worldwide

Additional information

FUNCTIONS	Wall-mounting distribution system Additional equipment
SPECIAL FEATURES	• Closed • Mounting from front, fast mounting, hinges on left or right possible • Door opening angle 167° • 1-point long with three-point turn-lock
USED WITH	Accessory Service distribution board IVS Accessory consideration Wall-mounting distribution system

Technical data - mechanical

COVER/DOOR TYPE	Three-point turn-lock
HOUSING MATERIAL	Sheet steel
MATERIAL	Sheet steel Steel
MOUNTING METHOD	Surface mounting
SUITABLE FOR HEIGHT	1260 mm
SUITABLE FOR WIDTH	600 mm
SURFACE FINISHING	Powder coating With powder coating
UNIT TYPE	Modular system
DEGREE OF PROTECTION	IP30 NEMA Other

Delivery programme

ACCESSORY/SPARE PART TYPE	Doors
COLOR	White Traffic white (RAL 9016)
MODEL	Stop door
TYPE	Additional equipment for wall-mounted service distribution board IVS

Resources

BROCHURES	eaton-xenergy-basic-light-brochure-br014024-en-us.pdf
CATALOGUES	eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf
FLYERS	eaton-xenergy-basic-profisnap-flyer-fl019008en-en-us.pdf
SALES NOTES	eaton-f3a-flange-flyer-fl019005en-en-us.pdf

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

