

Specifications



Eaton 292457

Eaton xEnergy Basic LV systems Low voltage switchgear. Sheet steel door transparent with rotary door handle HxW=1000x600mm, white

General specifications

PRODUCT NAME	Eaton xEnergy Basic door
CATALOG NUMBER	292457
MODEL CODE	BP-DT-600/10-W
EAN	4015082924577
PRODUCT LENGTH/DEPTH	38 mm
PRODUCT HEIGHT	1000 mm
PRODUCT WIDTH	600 mm
PRODUCT WEIGHT	2.8 kg
COMPLIANCES	RoHS conform



Powering Business Worldwide

Additional information

FEATURES	Version as glazed door
FUNCTIONS	Wall-mounting distribution system Additional equipment
SPECIAL FEATURES	Transparent doors
USED WITH	Accessory consideration Wall-mounting distribution system Service distribution board IVS Accessory

Technical data - mechanical

COVER/DOOR COLOR	Transparent
COVER/DOOR TYPE	Three-point turn-lock
HOUSING MATERIAL	Sheet steel/plastic
MATERIAL	Steel Sheet steel/plastic
MOUNTING METHOD	Surface mounting
SUITABLE FOR HEIGHT	1060 mm
SUITABLE FOR WIDTH	600 mm
SURFACE FINISHING	Powder coating With powder coating
UNIT TYPE	Modular system
DEGREE OF PROTECTION	IP30 NEMA Other

Delivery programme

ACCESSORY/SPARE PART TYPE	Doors
COLOR	Traffic white (RAL 9016) White
MODEL	Stop door
TYPE	Additional equipment for wall-mounted service distribution board IVS

Resources

BROCHURES	eaton-xenergy-basic-light-brochure-br014024-en-us.pdf
CATALOGUES	eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf
FLYERS	eaton-xenergy-basic-profisnap-flyer-fl019008en-en-us.pdf
SALES NOTES	eaton-f3a-flange-flyer-fl019005en-en-us.pdf

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

