

# Specifications

## Eaton 293558



Eaton xEnergy Basic LV systems Low voltage switchgear. Cable entry / flange plate for W=1000mm, closed

### General specifications

|                             |                                     |
|-----------------------------|-------------------------------------|
| <b>PRODUCT NAME</b>         | Eaton xEnergy Basic other accessory |
| <b>CATALOG NUMBER</b>       | 293558                              |
| <b>MODEL CODE</b>           | BP-FLP-1000-BL                      |
| <b>EAN</b>                  | 4015082935580                       |
| <b>PRODUCT LENGTH/DEPTH</b> | 168 mm                              |
| <b>PRODUCT HEIGHT</b>       | 10 mm                               |
| <b>PRODUCT WIDTH</b>        | 940 mm                              |
| <b>PRODUCT WEIGHT</b>       | 1.3 kg                              |
| <b>COMPLIANCES</b>          | RoHS conform                        |

## Additional information

|                  |                      |
|------------------|----------------------|
| <b>FUNCTIONS</b> | Additional equipment |
|------------------|----------------------|

## Technical data - mechanical

|                         |       |
|-------------------------|-------|
| <b>CABLE ENTRY TYPE</b> | Blind |
|-------------------------|-------|

|                         |             |
|-------------------------|-------------|
| <b>HOUSING MATERIAL</b> | Sheet steel |
|-------------------------|-------------|

|                 |                      |
|-----------------|----------------------|
| <b>MATERIAL</b> | Steel<br>Sheet steel |
|-----------------|----------------------|

|                        |                  |
|------------------------|------------------|
| <b>MOUNTING METHOD</b> | Surface mounting |
|------------------------|------------------|

|                                  |   |
|----------------------------------|---|
| <b>NUMBER OF CONNECTOR HOLES</b> | 0 |
|----------------------------------|---|

|              |          |
|--------------|----------|
| <b>SHAPE</b> | Straight |
|--------------|----------|

|                                               |    |
|-----------------------------------------------|----|
| <b>SUITABLE FOR NOMINAL THREAD (PG) - MAX</b> | 50 |
|-----------------------------------------------|----|

|                                               |    |
|-----------------------------------------------|----|
| <b>SUITABLE FOR NOMINAL THREAD (PG) - MIN</b> | 10 |
|-----------------------------------------------|----|

|                           |         |
|---------------------------|---------|
| <b>SUITABLE FOR WIDTH</b> | 1000 mm |
|---------------------------|---------|

|                          |                     |
|--------------------------|---------------------|
| <b>SURFACE FINISHING</b> | With powder coating |
|--------------------------|---------------------|

|                           |                |
|---------------------------|----------------|
| <b>SURFACE PROTECTION</b> | Powder coating |
|---------------------------|----------------|

|                  |      |
|------------------|------|
| <b>THICKNESS</b> | 1 mm |
|------------------|------|

|                    |      |
|--------------------|------|
| <b>THREAD TYPE</b> | None |
|--------------------|------|

|                             |               |
|-----------------------------|---------------|
| <b>DEGREE OF PROTECTION</b> | IP30<br>Other |
|-----------------------------|---------------|

## Delivery programme

|              |                       |
|--------------|-----------------------|
| <b>COLOR</b> | Light gray (RAL 7035) |
|--------------|-----------------------|

|              |       |
|--------------|-------|
| <b>MODEL</b> | Blind |
|--------------|-------|

|             |                      |
|-------------|----------------------|
| <b>TYPE</b> | Additional equipment |
|-------------|----------------------|

## Resources

|                  |                                                                       |
|------------------|-----------------------------------------------------------------------|
| <b>BROCHURES</b> | <a href="#">eaton-xenergy-basic-light-brochure-br014024-en-us.pdf</a> |
|------------------|-----------------------------------------------------------------------|

|                   |                                                                                      |
|-------------------|--------------------------------------------------------------------------------------|
| <b>CATALOGUES</b> | <a href="#">eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf</a> |
|-------------------|--------------------------------------------------------------------------------------|

|               |                                                                          |
|---------------|--------------------------------------------------------------------------|
| <b>FLYERS</b> | <a href="#">eaton-xenergy-basic-profisnap-flyer-fl019008en-en-us.pdf</a> |
|---------------|--------------------------------------------------------------------------|

|                    |                                                             |
|--------------------|-------------------------------------------------------------|
| <b>SALES NOTES</b> | <a href="#">eaton-f3a-flange-flyer-fl019005en-en-us.pdf</a> |
|--------------------|-------------------------------------------------------------|

|                      |
|----------------------|
| <b>PROJECT NAME:</b> |
|----------------------|

|                        |
|------------------------|
| <b>PROJECT NUMBER:</b> |
|------------------------|

|                     |
|---------------------|
| <b>PREPARED BY:</b> |
|---------------------|

|              |
|--------------|
| <b>DATE:</b> |
|--------------|



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

