

## Han Q 7/0-F



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                               |
|--------------------|-------------------------------------------------------------------------------|
| Part number        | 09 12 007 3101                                                                |
| Specification      | Han Q 7/0-F                                                                   |
| HARTING eCatalogue | <a href="https://harting.com/09120073101">https://harting.com/09120073101</a> |

### Identification

|                |                    |
|----------------|--------------------|
| Category       | Inserts            |
| Series         | Han <sup>®</sup> Q |
| Identification | 7/0                |

### Version

|                    |                                         |
|--------------------|-----------------------------------------|
| Termination method | Crimp termination                       |
| Gender             | Female                                  |
| Size               | 3 A                                     |
| Number of contacts | 7                                       |
| PE contact         | Yes                                     |
| Details            | Please order crimp contacts separately. |

### Technical characteristics

|                                            |                              |
|--------------------------------------------|------------------------------|
| Conductor cross-section (mm <sup>2</sup> ) | 0.14 ... 2.5 mm <sup>2</sup> |
| Rated current                              | 10 A                         |
| Rated voltage                              | 400 V                        |
| Rated impulse voltage                      | 6 kV                         |
| Pollution degree                           | 3                            |
| Rated voltage acc. to UL                   | 600 V                        |
| Rated voltage acc. to CSA                  | 600 V                        |
| Insulation resistance                      | >10 <sup>10</sup> Ω          |
| Limiting temperature                       | -40 ... +125 °C              |



**Pushing Performance**  
Since 1945

## Technical characteristics

Mating cycles  $\geq 500$

## Material properties

|                                           |                                                        |
|-------------------------------------------|--------------------------------------------------------|
| Material (insert)                         | Polycarbonate (PC)                                     |
| Colour (insert)                           | RAL 7032 (pebble grey)                                 |
| Material flammability class acc. to UL 94 | V-0                                                    |
| RoHS                                      | compliant with exemption                               |
| RoHS exemptions                           | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status                                | compliant with exemption                               |
| China RoHS                                | 50                                                     |
| REACH Annex XVII substances               | Not contained                                          |
| REACH ANNEX XIV substances                | Not contained                                          |
| REACH SVHC substances                     | Yes                                                    |
| REACH SVHC substances                     | Lead                                                   |
| ECHA SCIP number                          | 5dbb3851-b94e-4e88-97a1-571845975242                   |
| California Proposition 65 substances      | Yes                                                    |
| California Proposition 65 substances      | Lead                                                   |
| Fire protection on railway vehicles       | EN 45545-2 (2020-08) + A1 (2023-10)                    |
| Requirement set with Hazard Levels        | R22 (HL 1-3)<br>R23 (HL 1-3)                           |

## Specifications and approvals

|                |                                                            |
|----------------|------------------------------------------------------------|
| Specifications | IEC 60664-1<br>IEC 61984                                   |
| UL / CSA       | UL 1977 ECBT2.E235076<br>CSA-C22.2 No. 182.3 ECBT8.E235076 |
| Approvals      | DNV GL                                                     |

## Commercial data

|                                |                                                   |
|--------------------------------|---------------------------------------------------|
| Packaging size                 | 10                                                |
| Net weight                     | 11 g                                              |
| Country of origin              | Romania                                           |
| European customs tariff number | 85366990                                          |
| GTIN                           | 5713140017535                                     |
| eCl@ss                         | 27440205 Contact insert for industrial connectors |



**Pushing Performance**  
Since 1945

Commercial data

|             |          |
|-------------|----------|
| ETIM        | EC000438 |
| UNSPSC 24.0 | 39121522 |