


## Technical data sheet

Article number:  
111-00291

MBT20SFC



|                                    |                                                                                   |
|------------------------------------|-----------------------------------------------------------------------------------|
| <b>Product Group</b>               | Cable Ties with Ball-Lock and Coating                                             |
| <b>Product Family</b>              | MBT-FC-Series                                                                     |
| <b>Material</b>                    | Stainless Steel (SS316L), Polyester (SP)                                          |
| <b>Colour</b>                      | Black (BK)                                                                        |
| <b>Application Tool</b>            | KST-STG200, HDT16, MK9SST, MK9PSST                                                |
| <b>Bundle Ø max.</b>               | 152 mm                                                                            |
| <b>Bundle Ø min.</b>               | 17 mm                                                                             |
| <b>Flammability</b>                | non-burning (except coating), low smoke in accordance with CSA C22.2 No. 62275:21 |
| <b>Halogen-free</b>                | Yes                                                                               |
| <b>Length (L)</b>                  | 521 mm                                                                            |
| <b>Min.Tensile Strength</b>        | 540 N                                                                             |
| <b>Operating Temperature</b>       | -80 °C to +538 °C                                                                 |
| <b>Package Content</b>             | 100 pcs.                                                                          |
| <b>Package Content packed in</b>   | bag                                                                               |
| <b>Releasable Closure (Yes/No)</b> | No                                                                                |
| <b>Specifications</b>              | CSA -C22.2 no. 62275, UL 62275                                                    |
| <b>Thickness (T)</b>               | 0.38 mm                                                                           |
| <b>UL-File Number</b>              | E547605                                                                           |
| <b>UV-Stabilised</b>               | Yes                                                                               |
| <b>Variant</b>                     | Not Serrated                                                                      |
| <b>Weight/Unit</b>                 | 0.0053 kg                                                                         |
| <b>Width (W)</b>                   | 4.6 mm                                                                            |

