
HellermannTyton

# Technical data sheet

## Article number:
## 111-04805 T50R




| | |
|---|---|
| **Product Group** | Cable Ties Polyamide 6.6 standard |
| **Product Family** | T-Series in PA66 coloured |
| **Material** | Polyamide 6.6 (PA66) |
| **Colour** | Yellow (YE) |
| **Application Tool** | ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP, EVO9iHT |
| **Bundle Ø max.** | 50.0 mm |
| **Bundle Ø min.** | 1.5 mm |
| **Flammability** | UL 94 V2 |
| **Halogen-free** | Yes |
| **Length (L)** | 200 mm |
| **Min.Tensile Strength** | 225 N |
| **Operating Temperature** | -40 °C to +85 °C |
| **Package Content** | 100 pcs. |
| **Package Content packed in** | bag |
| **Releasable Closure (Yes/No)** | No |
| **Specifications** | IEC 62275 |
| **Thickness (T)** | 1.2 mm |
| **Toothing (Serration)** | Inside Serrated |
| **UV-Stabilised** | No |
| **Variant** | Inside Serrated |
| **Weight/Unit** | 0.0013 kg |
| **Width (W)** | 4.6 mm |

HF ✓ RoHS ✓

created on 22. May 2026, 10:39 am

Technical changes and errors reserved. It´s up to the customer to check the suitability for a specific application by means of tests.