
Technical data sheet

Article number:
111-12032 T120R(E)



Product Group	Cable Ties for higher impact resistant Polyamide 6.6 ScanBlack
Product Family	T-Series in PA66HIR(S)
Material	Polyamide 6.6, high impact modified, scan black (PA66HIR(S))
Colour	Black (BK)
Application Tool	ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT
Bundle Ø max.	100 mm
Bundle Ø min.	3.0 mm
Flammability	UL 94 HB
Halogen-free	Yes
Length (L)	387 mm
Min.Tensile Strength	535 N
Operating Temperature	-40 °C to +80 °C
Package Content	100 pcs.
Package Content packed in	bag
Releasable Closure (Yes/No)	No
Specifications	IEC 62275
Thickness (T)	1.8 mm
Toothing (Serration)	Inside Serrated
UV-resistant acc. to ASTM D6779 (Yes/No)	Yes
Variant	Inside Serrated
Weight/Unit	0.00586 kg
Width (W)	7.6 mm

HF RoHS EPD INTERNATIONAL EPD SYSTEM

created on 29. May 2026, 5:40 am

Technical changes and errors reserved. It´s up to the customer to check the suitability for a specific application by means of tests.