


## Technical data sheet

Article number:  
111-15660

**T150M**



|                                    |                                                                                                      |
|------------------------------------|------------------------------------------------------------------------------------------------------|
| <b>Product Group</b>               | Cable Ties for outdoor use (UV-resistant)                                                            |
| <b>Product Family</b>              | T-Series in PA66W black                                                                              |
| <b>Material</b>                    | Polyamide 6.6, UV-resistant (PA66W)                                                                  |
| <b>Colour</b>                      | Black (BK)                                                                                           |
| <b>Application Range</b>           | Outdoor Use                                                                                          |
| <b>Application Tool</b>            | ProCut 9 no battery, MK9P, MK9P w/ Upper air, MK10-SB, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT |
| <b>Bundle Ø max.</b>               | 150.0 mm                                                                                             |
| <b>Bundle Ø min.</b>               | 8.0 mm                                                                                               |
| <b>Flammability</b>                | UL 94 HB                                                                                             |
| <b>Halogen-free</b>                | Yes                                                                                                  |
| <b>Length (L)</b>                  | 530.0 mm                                                                                             |
| <b>Min.Tensile Strength</b>        | 780 N                                                                                                |
| <b>Operating Temperature</b>       | -40 °C to +85 °C                                                                                     |
| <b>Package Content</b>             | 25 pcs.                                                                                              |
| <b>Package Content packed in</b>   | pack                                                                                                 |
| <b>Releasable Closure (Yes/No)</b> | No                                                                                                   |
| <b>Specifications</b>              | UL 62275                                                                                             |
| <b>Thickness (T)</b>               | 2 mm                                                                                                 |
| <b>Toothing (Serration)</b>        | Inside Serrated                                                                                      |
| <b>UL-File Number</b>              | E64139                                                                                               |
| <b>UV-Stabilised</b>               | Yes [IEC62275]                                                                                       |
| <b>Variant</b>                     | Inside Serrated                                                                                      |
| <b>Weight/Unit</b>                 | 0.0112 kg                                                                                            |
| <b>Width (W)</b>                   | 8.9 mm                                                                                               |

