


## Technical data sheet

Article number:  
111-95209

MBT20XH



|                                    |                                                                      |
|------------------------------------|----------------------------------------------------------------------|
| <b>Product Group</b>               | Cable ties with ball-lock                                            |
| <b>Product Family</b>              | MBT-Series, stainless steel 316L                                     |
| <b>Material</b>                    | Stainless Steel (SS316L)                                             |
| <b>Colour</b>                      | Metal (ML)                                                           |
| <b>Application Range</b>           | High Temperature Environments                                        |
| <b>Application Tool</b>            | KST-STG200, HDT16, MK9SST, MK9PSST                                   |
| <b>Bundle Ø max.</b>               | 152.0 mm                                                             |
| <b>Bundle Ø min.</b>               | 12.0 mm                                                              |
| <b>Flammability</b>                | non-burning                                                          |
| <b>Halogen-free</b>                | Yes                                                                  |
| <b>Length (L)</b>                  | 521.0 mm                                                             |
| <b>Min.Tensile Strength</b>        | 2700 N                                                               |
| <b>Operating Temperature</b>       | -80 °C to +538 °C                                                    |
| <b>Package Content</b>             | 50 pcs.                                                              |
| <b>Package Content packed in</b>   | pack                                                                 |
| <b>Releasable Closure (Yes/No)</b> | No                                                                   |
| <b>Specifications</b>              | CSA -C22.2 no. 62275, IEC 60092, IEC 62275, IEC 62275:2022, UL 62275 |
| <b>Thickness (T)</b>               | 0.3 mm                                                               |
| <b>UL-File Number</b>              | E547605                                                              |
| <b>UV-Stabilised</b>               | Yes                                                                  |
| <b>Variant</b>                     | Not Serrated                                                         |
| <b>Weight/Unit</b>                 | 0.017658 kg                                                          |
| <b>Width (W)</b>                   | 12.3 mm                                                              |

