

## Technical data sheet

Article number:  
321-50680

TREDUX-HA47-68/22



|                                                 |                                                |
|-------------------------------------------------|------------------------------------------------|
| <b>Product Group</b>                            | Heat shrinkable tubing up to 4:1 - 1 m lengths |
| <b>Product Family</b>                           | TREDUX HA47 - thick wall adhesive lined        |
| <b>Material</b>                                 | Polyolefin, cross-linked (PO-X)                |
| <b>Colour</b>                                   | Black (BK)                                     |
| <b>Adhesive</b>                                 | Hot melt adhesive                              |
| <b>Dielectric Strength</b>                      | 20 kV/mm                                       |
| <b>Elongation at break (min.) [Test method]</b> | 400 % [ASTM D2671]                             |
| <b>Longitudinal Change After Shrinkage</b>      | -10% max.                                      |
| <b>Min. Shrink Temperature - °C</b>             | +120 °C                                        |
| <b>Operating Temperature</b>                    | -55 °C to +110 °C                              |
| <b>Package Content</b>                          | 1 pc.                                          |
| <b>Package Content packed in</b>                | pcs.                                           |
| <b>Recov. Ø d max.</b>                          | 22.0 mm                                        |
| <b>Shrink Ratio</b>                             | up to 4:1                                      |
| <b>Supplied Ø D min.</b>                        | 68.0 mm                                        |
| <b>Tensile Strength</b>                         | 14 MPa                                         |
| <b>Wall (WT)</b>                                | 4.1 mm                                         |

HF ✓

RoHS ✓