


drylin® R aluminium shaft | supported | AWMU | EN
AW 6061/6060
AWMU-40



drylin® R aluminium shaft | supported | AWMU
| EN AW 6061/6060

- Lightweight
- Optimal in combination with iglidur® J/J200 liners
- Low wear of plain bearings
- Corrosion-resistant
- Aluminium EN AW 6060/6061 (ALU)

Ø d1	9 mm
E	55 mm
max. length	4000 mm
V	8 mm
Part number	AWMU-40
Outer diameter d	40 mm
C5/C6 (min.)	20 mm
C5/C6 (max.)	119 mm
Angle Y	50 °
B	73 mm
Outer diameter (d) max. mm	9 mm
H	50 mm
Pitch T	200 mm

Product description

Introducing the drylin R aluminium shaft, supported AWMU, crafted from durable EN AW 6061/6060 aluminium. This lightweight shaft is designed for low wear and is corrosion-free, making it an ideal choice for various applications. It pairs perfectly with liners made from iglidur J/J200, ensuring optimal performance. Enhance your projects with this reliable and efficient aluminium shaft, built to last.

Manufacturing and installation tolerances

d tolerance	-0,1 mm
H-tolerance	±0,25 mm
E tolerance	±0.25mm



General properties

Material	Aluminium EN AW 6061/6060
Surface hardness	450-550 HV
Surface roughness Ra	< 0.6µm
Roundness	≤ 1/2 ø Tolerance
Drilling pattern	Standard

Dimensions

Outer diameter d	40 mm
Ø d1	9 mm
B	73 mm
V	8 mm
E	55 mm
Pitch T	200 mm
C5/C6 (min.)	20 mm
C5/C6 (max.)	119 mm
max. length	4000 mm
Angle Y	50 °
V	8 mm

Certificates and standards



Additional information and diagrams

