


Harnessed SPE cables, PUR 12.5xd, connector A:
Yamaichi, connector B: Yamaichi

CAT9471003



Harnessed SPE cables, PUR 12.5xd, connector
A: Yamaichi, connector B: Yamaichi

Product description

Introducing the Harnessed SPE Cables from our premium series, featuring a durable PUR outer jacket. Designed for medium-duty applications, these cables excel in both indoor and outdoor environments (excluding direct sunlight). With Yamaichi connectors on both ends, they offer exceptional oil resistance, notch resistance, and flame-retardant properties. Ideal for machine tools and low-temperature applications, they guarantee 10 million double strokes, making them a reliable choice for your connectivity needs.

General properties

Bus system	Single Pair Ethernet/CAT5e
Number of cores and conductor nominal cross-section	(2x0.15)C
Outer diameter (d) max. mm	5.5 mm
Weight per km	33 kg/km
Copper index kg/km	12 kg/km

Electricity attributes

Nominal voltage	50V
UL Voltage Rating	300 V
Test voltage	500V



Properties and approvals

UV resistance	Medium
Oil resistance	Oil-resistant (according to DIN EN 50363-10-2), Class 3
Offshore	MUD-resistant according to NEK 606 - status 2018
Flame-retardant	According to IEC 60332-1-2, Cable Flame, VW-1, FT1, FT2/Horizontal Flame
Silicone-free	Free from silicone which can affect paint adhesion (according to PV 3.10.7 – status 1992)
Halogen-free	According to DIN EN 60754
UL verified	Certificate no. V293650: "The igus 4-year chainflex cable guarantee and service life calculator based on 2 billion test cycles per year"
UL-Listed	CMX UL 444, 75°C
NFPA	According to NFPA 79-2018, chapter 12.9
DNV	Type Approval Certificate TAE00003X8
Lead-free	According to 2011/65/EU (RoHS-II/RoHS-III)
Cleanroom	According to ISO Class 1. The outer jacket material of this series complies with CF77.UL.05.12.D - tested by IPA according to standard DIN EN ISO 14644-1
DESINA	According to VDW, DESINA standardisation
CE	According to 2014/35/EU

Cable structure

Conductor	Stranded conductor in an especially bend-resistant version consisting of bare copper wires (according to DIN EN 60228).
Core insulation	According to bus specification.
 Conductor colours	According to bus specification.
Core group 1 core structure	2x0.15
Core group 1 colour code	white/blue
Overall shield	Bend-resistant braiding made of tinned copper wires. Coverage approx. 55% linear, approx. 80% optical
Outer jacket	Low-adhesion, halogen-free, highly abrasion-resistant PUR mixture, adapted to suit the requirements in e-chains® (according to DIN EN 50363-10-2).
Outer jacket colour	Red lilac (comparable to RAL 4001)



Dynamic properties

	Min. bend radius, e-chain (factor)	12.5 x d
	Min. bend radius, e-chain	68.75 mm
	Min. bend radius, flexible (factor)	10 x d
	Min. bend radius, fixed (factor)	7 x d
	Temperature e-chain®	-20°C up to +70°C
	Temperature, flexible	-40°C to +70°C (according to DIN EN 60811-504)
	Temperature, fixed	-50°C to +70°C (according to DIN EN 50305)
	v max. unsupported (speed)	3 m/s
v max. gliding (speed)		2 m/s
	a max. (acceleration)	30 m/s ²
	travel length	Class 3
	torsion	No torsion



chainflex®Lifetime

Guaranteed service life for this series according to guarantee conditions

Further information: [chainflex® guarantee](#)

Double strokes*	5 million	7.5 million	10 million
Temperature,	R min.	R min.	R min.
from/to [°C]	[Factor x d]	[Factor x d]	[Factor x d]
-20 / -10	15	16	17
-10 / +60	12.5	13.5	14.5
+60 / +70	15	16	17

* Higher number of double strokes possible - use the service life calculation function on this page.

Technical note on bus cables

chainflex® bus cables have been specially developed and tested for continuously moving use in e-chains® applications. Depending on the outer jacket material and the design principle, the bus cables are designed for different mechanical requirements and media resistance. The cables have been electrically designed in such a way that, on the one hand, the electrical requirements of the respective bus specification are reliably met and, on the other, that great value is placed on a high degree of EMC reliability. It is also ensured that the electrical values remain stable over the long term in spite of permanent movement. However, the overall quality of transmission in a complete bus communication system is not solely dependent on the cable used. Rather, it requires precise co-ordination of all components (electronic components,

connection technology and cable) as well as observing the maximum transmission levels depending on the respective systems in relation to the required data transmission rates. A cable is therefore not solely responsible for the secure transmission of signals.

igus® advises you when you are designing your bus system to take all these factors into account and, with extensive tests, helps you to ensure the process reliability of your system from the very beginning.

Certificates and standards

