

Drawing




Cable

Cable length [m]	3
Outer diameter (d) max. [mm]	5.5
Jacket material	TPE
Unshielded	Yes
Min. bend radius, flexible [MM]	22
Min. bend radius, fixed [MM]	16.5
Number of cores and conductor nominal cross section	5x0.34
Main cable	CF9.03.05.INI

For further data, see basic cable.

Connector Specification

Plug type	M12		
Plug version	straight		
Motor cable			
M12 5-pole			
Pin	Colour	Signal	
		ST	DC
1	brown	A/	+
2	white	A	
3	blue	B	-
4	black	B/	
5	green-yellow	PE	



Suitable motors with plug

- MOT-AD-S-060-017-056-M-A-AAAK
- MOT-AN-S-060-001-028-M-A-AAAA
- MOT-AN-S-060-005-042-M-A-AAAA
- MOT-AN-S-060-020-056-M-A-AAAA
- MOT-AN-S-060-035-060-M-A-AAAA
- MOT-DC-36-M-A-D
- MOT-DC-37-M-A-A
- MOT-DC-37-M-A-B
- MOT-DC-37-M-A-D
- MOT-DC-37-M-A-H
- MOT-DC-42-M-A-D
- MOT-DC-42-M-A-F

Suitable motors with plug encoder

- MOT-AD-S-060-017-056-M-C-AAAL
- MOT-AN-S-060-005-042-M-C-AAAC
- MOT-AN-S-060-005-042-M-C-AAAS
- MOT-AN-S-060-020-056-M-C-AAAC
- MOT-AN-S-060-020-056-M-C-AAAS
- MOT-AN-S-060-035-060-M-C-AAAC
- MOT-AN-S-060-035-060-M-C-AAAS

Suitable motors with plug encoder brake

- MOT-AN-S-060-005-042-M-D-AAAD
- MOT-AN-S-060-020-056-M-D-AAAD
- MOT-AN-S-060-035-060-M-D-AAAD