

Drawing




Cable

Cable length [m]	3
Outer diameter (d) max. [mm]	7.5
Jacket material	TPE
Unshielded	No
Min. bend radius, flexible [MM]	37.5
Min. bend radius, fixed [MM]	30
Number of cores and conductor nominal cross section	(4x(2x0,14))C
Main cable	CF11.01.04.02

For further data, see basic cable.

Connector Specification

Plug type	JST ZHR-8	
Plug version	straight	
Encoder cable		
JST ZHR-8		
PIN	Colour	Signal
1	blue	0V
2	red	5V DC
3	white	A
4	brown	A/
5	green	B/
6	yellow	B
7	grey	N/
8	pink	N



Suitable motors with plug

--

Suitable motors with plug encoder

• MOT-AN-S-060-001-035-L-C-AAAO • MOT-AN-S-060-002-035-L-C-AAAC • MOT-AN-S-060-002-042-L-C-AAAO • MOT-AN-S-060-005-042-L-C-AAAC • MOT-AN-S-060-010-056-L-C-AAAO • MOT-AN-S-060-016-060-L-C-AAAO • MOT-AN-S-060-020-056-L-C-AAAC • MOT-AN-S-060-035-060-L-C-AAAC • MOT-AN-S-060-036-086-L-C-AAAO • MOT-AN-S-060-059-086-L-C-AAAC • MOT-ST-28-L-C-A • MOT-ST-28-L-C-B • MOT-ST-35-L-C-A • MOT-ST-35-L-C-B • MOT-ST-42-L-C-A • MOT-ST-42-L-C-B • MOT-ST-56-L-C-A • MOT-ST-56-L-C-B

Suitable motors with plug encoder brake

--