

Drawing




Cable

Cable length [m]	3
Outer diameter (d) max. [mm]	5.5
Jacket material	TPE
Unshielded	Yes
Min. bend radius, flexible [MM]	22
Min. bend radius, fixed [MM]	16.5
Number of cores and conductor nominal cross section	5x0.34
Main cable	CF9.03.05.INI

For further data, see basic cable.

Connector Specification

Plug type	JST B4B-XH-A	
Plug version	straight	
Motor cable		
JST B4B-XH-A		
PIN	Colour	Signal
1	white	A
2	brown	A/
3	blue	B
4	black	B/



Suitable motors with plug

- MOT-AN-S-060-001-020-L-A-AAAA
- MOT-AN-S-060-001-028-L-A-AAAA
- MOT-AN-S-060-001-028-L-A-AAAO
- MOT-AN-S-060-001-035-L-A-AAAO
- MOT-AN-S-060-002-035-L-A-AAAA
- MOT-AN-S-060-002-035-L-B-AAAA
- MOT-AN-S-060-002-042-L-A-AAAO
- MOT-AN-S-060-005-042-L-A-AAAA
- MOT-AN-S-060-005-042-L-A-AAAB
- MOT-AN-S-060-010-056-L-A-AAAO
- MOT-AN-S-060-016-060-L-A-AAAO
- MOT-AN-S-060-020-056-L-A-AAAA
- MOT-AN-S-060-020-056-L-A-AAAB
- MOT-AN-S-060-035-060-L-A-AAAA
- MOT-AN-S-060-035-060-L-A-AAAB
- MOT-ST-20-L-A-B
- MOT-ST-28-L-A-A
- MOT-ST-28-L-A-B
- MOT-ST-35-L-A-A
- MOT-ST-35-L-A-B
- MOT-ST-42-L-A-A
- MOT-ST-42-L-A-B
- MOT-ST-56-L-A-A
- MOT-ST-56-L-A-B

Suitable motors with plug encoder

- MOT-AN-S-060-001-035-L-C-AAAO
- MOT-AN-S-060-002-035-L-C-AAAC
- MOT-AN-S-060-002-042-L-C-AAAO
- MOT-AN-S-060-005-042-L-C-AAAC
- MOT-AN-S-060-010-056-L-C-AAAO
- MOT-AN-S-060-016-060-L-C-AAAO
- MOT-AN-S-060-020-056-L-C-AAAC
- MOT-AN-S-060-035-060-L-C-AAAC
- MOT-AN-S-060-036-086-L-C-AAAO
- MOT-AN-S-060-059-086-L-C-AAAC
- MOT-ST-28-L-C-A
- MOT-ST-28-L-C-B
- MOT-ST-35-L-C-A
- MOT-ST-35-L-C-B
- MOT-ST-42-L-C-A
- MOT-ST-42-L-C-B
- MOT-ST-56-L-C-A
- MOT-ST-56-L-C-B

Suitable motors with plug encoder brake

- MOT-AN-S-060-002-035-L-B-AAAA
- MOT-AN-S-060-005-042-L-B-AAAA
- MOT-AN-S-060-020-056-L-B-AAAA
- MOT-AN-S-060-035-060-L-B-AAAA
- MOT-AN-S-060-059-086-L-B-AAAA
- MOT-AN-S-060-112-086-L-B-AAAA