

Drawing



Cable

Cable length [m]	3
Outer diameter (d) max. [mm]	7
Jacket material	TPE
Unshielded	Yes
Min. bend radius, flexible [MM]	70
Min. bend radius, fixed [MM]	49
Number of cores and conductor nominal cross section	5G0,75
Main cable	CF880.07.05

For further data, see basic cable.

Connector Specification

Plug type	Molex 469930411
Plug version	straight
Motor cable	
Molex 469930411	
PIN	Signal
1	A
2	A/
3	B
4	B/



Suitable motors with plug

- MOT-AN-S-060-036-086-L-A-AAO
- MOT-AN-S-060-036-086-L-C-AAO
- MOT-AN-S-060-059-086-L-A-AAAB
- MOT-AN-S-060-059-086-L-B-AAAB
- MOT-AN-S-060-059-086-L-C-AAAC
- MOT-AN-S-060-112-086-L-A-AAAB
- MOT-AN-S-060-112-086-L-B-AAAB
- MOT-AN-S-060-112-086-L-C-AAAC
- MOT-ST-42-C-A-C
- MOT-ST-56-C-A-C
- MOT-ST-60-C-A-C
- MOT-ST-86-C-A-C

Suitable motors with plug encoder

- MOT-AN-S-060-036-086-L-C-AAO
- MOT-AN-S-060-059-086-L-C-AAAC
- MOT-AN-S-060-112-086-L-C-AAAC
- MOT-ST-42-C-C-C
- MOT-ST-56-C-C-C
- MOT-ST-60-C-C-C
- MOT-ST-86-C-C-C

Suitable motors with plug encoder brake

- MOT-AN-S-060-059-086-L-B-AAAB
- MOT-AN-S-060-112-086-L-B-AAAB