


drylin® R stainless steel shaft | supported | EWUM |
AISI 440B

EWUM-12



drylin® R stainless steel shaft | supported |
EWUM | AISI 440B

- High corrosion resistance
- High chemical resistance
- Ideal solution for wet applications
- Stainless steel AISI 440B (high grade steel)
- Aluminium support

V	5 mm
N1	8 mm
N2	5 mm
M	5.8 mm
E	29 mm
Pitch T	120 mm
Angle Y	50 °
B	40 mm
Ø d1	4.5 mm
H	22 mm
Outer diameter d	12 mm
C5/C6 (min.)	20 mm
C5/C6 (max.)	79 mm

Product description

Introducing the drylin R stainless steel shaft, supported, EWUM, crafted from high-grade AISI 440B stainless steel. This shaft offers exceptional corrosion and chemical resistance, making it the ideal choice for wet applications. The durable aluminum support enhances its reliability, ensuring long-lasting performance. Upgrade your projects with this robust and efficient solution that stands up to challenging environments.

Manufacturing and installation tolerances

d tolerance	h6
H-tolerance	±0,02 mm

General properties

Drilling pattern	Standard
------------------	----------



Dimensions

Outer diameter d	12 mm
Ø d1	4.5 mm
B	40 mm
V	5 mm
N1	8 mm
N2	5 mm
M	5.8 mm
E	29 mm
Pitch T	120 mm
C5/C6 (min.)	20 mm
C5/C6 (max.)	79 mm
max. length	6000 mm
Angle Y	50 °
V	5 mm

Certificates and standards

