


drylin® R stainless steel shaft | partially supported
| EWUM-ES | AISI 440B

EWUM-ES-12



drylin® R stainless steel shaft | partially supported | EWUM-ES | AISI 440B

- High corrosion resistance
- High chemical resistance
- Ideal solution for wet applications
- Stainless steel AISI 440B (high grade steel)

Outer diameter d	12 mm
Ø d1	4.5 mm
B	40 mm
Pitch T	120 mm
C5/C6 (min.)	20 mm
C5/C6 (max.)	79 mm
max. length	6000 mm
Part number	EWUM-ES-12
V	5 mm
E	29 mm
F	5.8 mm
G	14 mm

Product description

Introducing the drylin R stainless steel shaft, partially supported, EWUM-ES, crafted from high-grade AISI 440B stainless steel. This shaft offers exceptional corrosion and chemical resistance, making it the perfect choice for wet applications. Its durable construction ensures reliability and longevity, even in challenging environments. Upgrade your projects with this robust and versatile solution that combines strength with superior performance.

Manufacturing and installation tolerances

d tolerance	h6
H-tolerance	±0,02 mm

General properties

Material	Stainless steel AISI 440B (high grade steel)
Drilling pattern	Standard



Dimensions

Outer diameter d	12 mm
Ø d1	4.5 mm
B	40 mm
V	5 mm
E	29 mm
Pitch T	120 mm
C5/C6 (min.)	20 mm
C5/C6 (max.)	79 mm
max. length	6000 mm
V	5 mm
F	5.8 mm
G	14 mm

Certificates and standards



Additional information and diagrams

