


drylin® R stainless steel shaft | partially supported
| EWUMS-ES | AISI 316Ti
EWUMS-ES-12



drylin® R stainless steel shaft | partially supported | EWUMS-ES | AISI 316Ti

- High corrosion resistance
- High chemical resistance
- Ideal solution for wet applications
- Stainless steel 1.4571 (V4A)

Outer diameter d	12 mm
Ø d1	4.5 mm
B	40 mm
V	5 mm
E	29 mm
F	5.8 mm
G	14 mm
Pitch T	120 mm
C5/C6 (min.)	20 mm
C5/C6 (max.)	79 mm
max. length	3000 mm
Part number	EWUMS-ES-12

Product description

Introducing the drylin R stainless steel shaft, partially supported, model EWUMS-ES, crafted from high-quality AISI 316Ti (1.4571 V4A) stainless steel. This shaft boasts exceptional corrosion and chemical resistance, making it the ideal solution for wet applications. Its durable design ensures reliable performance in challenging environments, providing you with the confidence you need for your projects. Choose drylin for superior quality and resilience.

Manufacturing and installation tolerances

d tolerance	h9
H-tolerance	±0,03 mm

General properties

Material	Stainless steel 1.4571 (V4A)
Surface roughness Ra	0,3 - 0,6 µm
Drilling pattern	Standard



Dimensions

Outer diameter d	12 mm
Ø d1	4.5 mm
B	40 mm
V	5 mm
E	29 mm
Pitch T	120 mm
C5/C6 (min.)	20 mm
C5/C6 (max.)	79 mm
max. length	3000 mm
V	5 mm
F	5.8 mm
G	14 mm

Certificates and standards



Additional information and diagrams

