

## Clevis joint combination: GARMK-10



### Order key

| Type                        | Size |
|-----------------------------|------|
| <b>G A R M K - 10</b>       |      |
| Clevis joint                |      |
| Male thread                 |      |
| Thread                      |      |
| Metric                      |      |
| With clevis pin and circlip |      |
| Inner Ø [mm]                |      |

### Can be combined with:

- Safety bolt GBM-10 and circlip GSR-10 - part number GARMK-10
- As clevis joint combination with rod end bearing EARM-10 - part number GARMKE-10
- All igubal® parts with female thread M10



### Material:

igumid® G ► Page 1190



### Online service life calculation

► [www.igus.eu/igubal-expert](http://www.igus.eu/igubal-expert)

## Technical data

| Part No.        | Max. static tensile strain |           | Max. static axial force |           | Weight<br>[g] |
|-----------------|----------------------------|-----------|-------------------------|-----------|---------------|
|                 | Short-term                 | Long-term | Short-term              | Long-term |               |
|                 | [N]                        | [N]       | [N]                     | [N]       |               |
| <b>GARMK-10</b> | 3,000                      | 1,500     | 200                     | 100       | 15.7          |

Clevis joints with spring-loaded fixing clip in combination with E series rod ends, EARM ► Page 890