


drylin® flange lead screw nut, thermoplastic ACME,
J350FRI

J350FRI-01-1-5



drylin® flange lead screw nut, thermoplastic
ACME, J350FRI

- Material: iglide® J350
- Thread direction: Right-hand thread
- Thread type: ACME
- Design: Standard
- Cylindrical lead screw nut with flange

Product description

Introducing the drylin flange lead screw nut, made from high-performance iglidur J350 thermoplastic. This durable nut is designed for medium to high temperatures, withstanding up to +150°C while remaining dimensionally stable. It offers a lubrication-free, maintenance-free experience and is resistant to chemicals and wear. Ideal for various applications, it ensures quiet and vibration-free operation, making it perfect for demanding environments. Upgrade your systems with this reliable and efficient lead screw nut.

Requirements

Mould-resistant according to DIN EN ISO 846 Procedure A	Yes
---	-----

Thermal properties

Efficiency [η]	20-27
----------------	-------

General properties

Thread direction	Right-hand thread
Thread type	ACME; US standard
With spanner flat	No
Weight	278.85 g



Dimensions

Thread size	1-5
Ø d1	1 in
Ø d2	1.5 in
Ø d3	2.5 in
Ø d4	2 in
Ø d5	0.28 in
b2	0.59 in