


drylin® R liner JUM-01

JUM-01-10



drylin® R liner JUM-01

- Material: iglidur® J for all shaft surfaces in indoor and outdoor use
- Version: enclosed housing, long design

Ø z	2.5 mm
t	0.8 mm
r	3 mm
Part number	JUM-01-10

Product description

Introducing the drylin R liner JUM-01, a reliable solution for both indoor and outdoor applications. Crafted from iglidur J material, it ensures durability across various shaft surfaces. Its enclosed housing design adds to its long-lasting performance, making it an ideal choice for your needs. Experience the perfect blend of functionality and resilience with the drylin R liner JUM-01.

Requirements

Mould-resistant according to DIN EN ISO 846 Procedure A	Yes
---	-----

Physical properties

Max. long-term application temperature	90 °C
Lower application temperature	-50 °C

Manufacturing and installation tolerances

d1 tolerance	+0.030 +0.070mm
di tolerance	H7
B tolerance	h10
r1 tolerance	+0,05 mm
t1 tolerance	+0,1 mm
f1 tolerance	+0,5 mm





Dimensions

Ø d1	10 mm
Ø d2	12 mm
b1	28 mm
r	3 mm
t	0.8 mm
Ø z	2.5 mm
Ø di	12 mm
B	29 mm
t1	1 mm
Ø Z1	2.6 mm

Certificates and standards



Additional information and diagrams



Mounting hole for sliding film JUM-01

Welle/shaft	d1	B	r	t	f	Z	Art.-Nr./Article number
Ø	H7	h10	+0,05	+0,1	+0,5	+0,2	
10	12	29	0,0	1,0	1,0	2,0	JUM-01-10
12	14	32	0,0	1,0	1,5	3,1	JUM-01-12
16	18	36	0,5	1,0	1,7	3,6	JUM-01-16
20	22	40	0,0	1,0	2,0	3,6	JUM-01-20
25	28	50	0,0	1,0	2,0	4,1	JUM-01-25
30	34	58	0,0	1,0	2,0	4,1	JUM-01-30
35	39	70	0,0	1,0	2,0	4,1	JUM-01-35
40	44	80	0,0	1,5	2,5	5,1	JUM-01-40
50	55	100	0,0	1,5	2,5	6,1	JUM-01-50
60	65	125	0,0	2,5	3,0	6,5	JUM-01-60