

readycable® servo cable suitable for LTi DRIVES

KGH3-KSxxx (ext.), extension cable TPE 10xd

MAT9023011



readycable® servo cable suitable for LTi

DRIVES KGH3-KSxxx (ext.), extension cable

TPE 10xd

- For extremely heavy duty applications
- TPE outer jacket
- Oil-resistant (following DIN EN 60811-404), resistant to bio oils (following VDMA 24568 with Plantocut 8 S-MB tested by DEA)
- Halogen-free
- Silicone-free
- Hydrolysis and microbe-resistant
- PVC-free
- CFRIP®
- Guarantee up to 4 years

Product description

Introducing the readycable® servo cable, specifically designed for LTi DRIVES KGH3-KSxxx. This extension cable features a robust TPE outer jacket, making it perfect for extremely heavy-duty applications. It offers exceptional oil resistance, including bio-oils, and is suitable for both indoor and outdoor use without direct sunlight. With hydrolysis and microbe resistance, this halogen-free and silicone-free cable ensures reliable performance in demanding environments. Ideal for storage units, machining tools, and low-temperature applications.

Manufacturer attributes

Manufacturer Part No	KGH3-KSxxx (ext.)
Cable type	Extension cable

Connectors

Connector A	round plug, socket
Connector B	coupling, pin



General properties

Number of cores and conductor nominal cross-section	(4x(2x0.25)+2x1.0)C
Outer diameter (d) max. mm	9 mm
Weight per km	105 kg/km
Copper index kg/km	68 kg/km


Electricity attributes

	Nominal voltage	50V
UL Voltage Rating		300 V
	Test voltage	1500V (according to DIN EN 50395)



Cable structure

	Conductor	Stranded conductor in an especially flexible design consisting of tinned copper wires (according to DIN EN 60228).
	Core insulation	Mechanically high-quality TPE mixture.
	Core stranding	According to measuring system specification
	Conductor colours	according to measuring system specification
Core group 1 core structure		4x(2x0.25)
Core group 1 colour code		brown/green, blue/violet, grey/pink, red/black
Core group 2 core structure		2x1.0
	Element shield	Extremely flexible braiding made of tinned copper wires. Coverage linear approx. 70%, optical approx. 90%
Element jacket		TPE mixture on pair shielding adapted to suit the requirements in e-chains®.
Inner jacket		TPE mixture adapted to suit the requirements in e-chains®.
	Overall shield	Extremely flexible braiding made of tinned copper wires. Coverage linear approx. 70%, optical approx. 90%
	Outer jacket	Low-adhesion, extremely abrasion-resistant and highly flexible TPE mixture, adapted to suit the requirements in e-chains®.
	Outer jacket colour	Yellow-green (comparable to RAL 6018)
	CFRIP®	Strip cables faster: a tear strip is moulded into the inner jacket



1. Outer jacket: pressure-extruded, halogen-free TPE mixture
2. Overall shield: extremely flexible braiding made of tinned copper wires
3. Inner jacket: pressure-extruded, gusset-filling TPE mixture
4. Element jacket: mechanically high-quality TPE mixture
5. Element shield: extremely flexible tinned copper wire
6. Banding: plastic foil
7. CFRIP: tear strip for faster stripping
8. Core insulation: mechanically high-quality TPE mixture
9. Conductor: stranded wire conductors in a particularly flexible design made of tinned copper wires
10. Strain relief: high tensile strength centre element



Properties and approvals

	UV resistance	Medium
	Oil resistance	Oil-resistant (according to DIN EN 60811-404), bio-oil-resistant (according to VDMA 24568 with Plantocut 8 S-MB tested by DEA), Class 4
	Silicone-free	Free from silicone which can affect paint adhesion (according to PV 3.10.7 – status 1992)
	Halogen-free	According to DIN EN 60754
	UL verified	Certificate no. V293650: "The igus 4-year chainflex cable guarantee and service life calculator based on 2 billion test cycles per year"
UL AWM		Style 10467 and 22355, 300 V, 80 °C
	REACH	In accordance with Regulation (EC) No. 1907/2006 (REACH)
	Lead-free	According to 2011/65/EU (RoHS-II/RoHS-III)
	Cleanroom	According to ISO Class 1. The outer jacket material of this series complies with CF9.15.07 - tested by IPA according to standard DIN EN ISO 14644-1
	DESINA	According to VDW, DESINA standardisation
	CE	According to 2014/35/EU



Dynamic properties

	Min. bend radius, e-chain (factor)	6.8 x d
	Min. bend radius, e-chain	61.2 mm
	Min. bend radius, flexible (factor)	5 x d
	Min. bend radius, fixed (factor)	4 x d
	Temperature e-chain®	-35°C up to +90°C
	Temperature, flexible	-50°C to +90°C (according to DIN EN 60811-504)
	Temperature, fixed	-55°C to +90°C (according to DIN EN 50305)
	v max. unsupported (speed)	10 m/s
	v max. gliding (speed)	6 m/s
	a max. (acceleration)	100 m/s ²
	travel length	Class 6
	torsion	No torsion



chainflex®Lifetime

Guaranteed service life for this series according to guarantee conditions

Further information: [chainflex® guarantee](#)

Double strokes*	5 million		7.5 million		12.5 million	
Temperature,	R min. [Factor x d]		R min. [Factor x d]		R min. [Factor x d]	
from/to [°C]	< 10 m	≥ 10 m	< 10 m	≥ 10 m	< 10 m	≥ 10 m
-35/-25	8.5	10	9.5	11	10.5	12
-25/+80	6.8	7.5	7.5	8.5	8.8	9.5
+80/+90	8.5	10	9.5	11	10.5	12

* Higher number of double strokes possible - use the service life calculation function on this page.

Certificates and standards

