

readycable® motor cable Kuka Fortec Titan angled
socket
MAT904105014



**readycable® motor cable Kuka Fortec Titan
angled socket**

- PUR outer jacket
- Shielded
- Oil-resistant and coolant-resistant
- Flame retardant
- PVC and halogen-free
- Notch-resistant
- Hydrolysis and microbe-resistant

Product description

Introducing the readycable® motor cable Kuka Fortec Titan angled socket, designed for reliable performance in demanding environments. This cable features a durable PUR outer jacket that is shielded, oil-resistant, and coolant-resistant. It's also flame retardant, PVC and halogen-free, notch-resistant, and resistant to hydrolysis and microbes. Ideal for use with the seventh robot axis, this cable ensures optimal electrical properties for KUKA, ABB, and Fanuc applications. Trust in its robust design for your automation needs.

General properties

Number of cores and conductor nominal cross-section	(2x(3x1.5)C+3x(3x10)+1G10)C
Outer diameter (d) max. mm	36 mm
Weight per km	2122 kg/km
Copper index kg/km	1340 kg/km


Electricity attributes

 Nominal voltage	600/1,000V (according to DIN VDE 0298-3)
UL Voltage Rating	1000 V
 Test voltage	4000V (according to DIN EN 50395)



Cable structure

	Conductor	Finely stranded conductor consisting of bare copper wires (according to DIN EN 60228).
	Core insulation	Mechanically high-quality TPE mixture.
Core group 1 core structure		2x(3x1.5)C
Core group 1 colour code		Black cores with white numerals 10-15
Core group 2 core structure		3x(3x10)
	Inner jacket	TPE mixture adapted to suit the requirements in e-chains®.
	Overall shield	Bend-resistant braiding made of tinned copper wires. Coverage approx. 50% linear, approx. 80% optical
	Outer jacket	Low-adhesion, halogen-free, highly abrasion-resistant PUR mixture, adapted to suit the requirements in e-chains® (according to DIN EN 50363-10-2).
	Outer jacket colour	Jet black (comparable to RAL 9005)



1. Outer jacket: pressure extruded PUR mixture
2. Overall shield: flexible braiding made of tinned copper wires.
3. Inner jacket: pressure extruded, gusset-filling TPE mixture
4. Element banding: synthetic fleece over plastic foil
5. Bundles with optimised pitch length and direction
6. Element shield: bend-resistant braiding of tinned copper wires
7. Element banding: plastic foil over plastic fleece
8. Core insulation: mechanically high-quality TPE mixture
9. Conductor: fine stranded wire made of bare copper wires



Dynamic properties

	Min. bend radius, e-chain (factor)	10 x d
	Min. bend radius, e-chain	355 mm
	Min. bend radius, flexible (factor)	8 x d
	Min. bend radius, fixed (factor)	5 x d
	Temperature e-chain®	-25°C up to +80°C
	Temperature, flexible	-40°C to +80°C (according to DIN EN 60811-504)
	Temperature, fixed	-50°C to +80°C (according to DIN EN 50305)
	v max. unsupported (speed)	3 m/s
	v max. gliding (speed)	2 m/s
	a max. (acceleration)	20 m/s ²
	torsion	No torsion



Properties and approvals

	UV resistance	High
	Oil resistance	Oil-resistant (according to DIN EN 50363-10-2), Class 3
	Offshore	MUD-resistant according to NEK 606 - status 2018
	Flame-retardant	According to IEC 60332-1-2, Cable Flame, VW-1, FT1, FT2/Horizontal Flame
	Silicone-free	Free from silicone which can affect paint adhesion (according to PV 3.10.7 – status 1992)
	Halogen-free	According to DIN EN 60754
	UL verified	Certificate no. B129699: "igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year"
	NFPA	According to NFPA 79-2018, chapter 12.9
	REACH	In accordance with Regulation (EC) No. 1907/2006 (REACH)
	CE	According to 2014/35/EU

Certificates and standards

