

Connection cable suitable for Keyence iOP-87361
PUR, 12.50xd
MAT904194291



Connection cable suitable for Keyence
iOP-87361 PUR, 12.50xd

Product description

Introducing the Connecting Cable suitable for Keyence iOP-87361 PUR, designed for medium duty applications. This cable features a durable PUR outer jacket, offering exceptional resistance to oil, flames, and coolants. Ideal for both indoor and outdoor use (without direct sunlight), it supports unsupported travel distances and gliding applications up to 20m. With a bend factor of 12.5xd and guaranteed for 10 million double strokes, this cable is perfect for processing and machine tools. Choose reliability and performance with this versatile connection solution.

General properties

Bus system	Ethernet/CAT6/PoE
Number of cores and conductor nominal cross-section	(4x(2x0.15))C
Outer diameter (d) max. mm	7.5 mm
Weight per km	66 kg/km
Copper index kg/km	33 kg/km

Electricity attributes

Nominal voltage	50V
UL Voltage Rating	300 V
Test voltage	500V



Properties and approvals

UV resistance	Medium
Oil resistance	Oil-resistant (according to DIN EN 50363-10-2), Class 3
Offshore	MUD-resistant according to NEK 606 - status 2018
Flame-retardant	According to IEC 60332-1-2, Cable Flame, VW-1, FT1, FT2/Horizontal Flame
Silicone-free	Free from silicone which can affect paint adhesion (according to PV 3.10.7 – status 1992)
Halogen-free	According to DIN EN 60754
UL verified	Certificate no. V293650: "The igus 4-year chainflex cable guarantee and service life calculator based on 2 billion test cycles per year"
UL-Listed	CMX UL 444, 75°C
UL/CSA AWM	Style 1598 and 20236, 30 V, 80 °C
NFPA	According to NFPA 79-2018, chapter 12.9
DNV	Type Approval Certificate TAE00003X8
Lead-free	According to 2011/65/EU (RoHS-II/RoHS-III)
Cleanroom	According to ISO Class 1. The outer jacket material of this series complies with CF77.UL.05.12.D - tested by IPA according to standard DIN EN ISO 14644-1
DESINA	According to VDW, DESINA standardisation
CE	According to 2014/35/EU

Cable structure

Conductor	Stranded conductor in an especially bend-resistant version consisting of bare copper wires (according to DIN EN 60228).
Core insulation	According to bus specification.
Conductor colours	white-blue/blue, white-orange/orange, white-green/green, white-brown/brown
Core group 1 core structure	4x(2x0.15)
Core group 1 colour code	white-blue/blue, white-orange/orange, white-green/green, white-brown/brown
Overall shield	Bend-resistant braiding made of tinned copper wires. Coverage approx. 55% linear, approx. 80% optical
Outer jacket	Low-adhesion, halogen-free, highly abrasion-resistant PUR mixture, adapted to suit the requirements in e-chains® (according to DIN EN 50363-10-2).
Outer jacket colour	Red lilac (comparable to RAL 4001)



Dynamic properties

Min. bend radius, e-chain (factor)	12.5 x d
Min. bend radius, e-chain	93.75 mm
Min. bend radius, flexible (factor)	10 x d
Min. bend radius, fixed (factor)	7 x d
Temperature e-chain®	-20°C up to +70°C
Temperature, flexible	-40°C to +70°C (according to DIN EN 60811-504)
Temperature, fixed	-50°C to +70°C (according to DIN EN 50305)
v max. unsupported (speed)	3 m/s
v max. gliding (speed)	2 m/s
a max. (acceleration)	30 m/s²
travel length	Class 3
torsion	No torsion

Certificates and standards

