

readycable® power cable suitable for Bosch
Rexroth RKL4311, extension cable PUR 7.5xd

MAT9091009



readycable® power cable suitable for Bosch
Rexroth RKL4311, extension cable PUR 7.5xd

- For extremely heavy duty applications
- PUR outer jacket
- Shielded
- Oil-resistant and coolant-resistant
- Notch-resistant
- Flame retardant
- Hydrolysis and microbe-resistant
- Guarantee up to 4 years

Product description

Introducing the readycable power cable, specifically designed for Bosch Rexroth RKL4311. This durable extension cable features a robust PUR outer jacket, making it ideal for heavy-duty applications. Its oil, coolant, and UV resistance ensure reliable performance indoors and outdoors. With flame-retardant and halogen-free properties, it's safe for various environments, including cleanrooms and low-temperature settings. Experience unmatched flexibility and resilience with this high-quality cable, perfect for demanding tasks.

Manufacturer attributes

Manufacturer Part No	RKL4311
Cable type	Extension cable

Connectors

Connector A	val_226
Connector B	M40 plug-in connector, pin, straight, 9-pin

General properties

Number of cores and conductor nominal cross-section	(4G1.5+2x(2x0.75)C)C
Outer diameter (d) max. mm	14.5 mm
Weight per km	287 kg/km
Copper index kg/km	167 kg/km



Electricity attributes



Nominal voltage

600/1,000V (according to DIN VDE 0298-3)

UL Voltage Rating

1000 V



Test voltage

4000V (according to DIN EN 50395)

Cable structure



Conductor

Stranded conductor in an especially bend-resistant version consisting of bare copper wires (according to DIN EN 60228).



Core insulation

Mechanically high-quality, especially low-capacity XLPE mixture.



Core stranding

Power cores with control pair elements wound with elements for high-tensile stresses.



Conductor colours

Power cores: Cores black with white digits, one core green-yellow. 1st core: U / L1 / C / L+ 2nd core: V / L2 3rd core: W / L3 / D / L- 2 control pairs: cores black with white digits. 1st control wire: 5 2nd control wire: 6 3rd control wire: 7 4th control wire: 8

Core group 1 core structure

4G1.5

Core group 2 core structure

2x(2x0.75)C)C



Element shield

Extremely bend-resistant braiding made of tinned copper wires.

Inner jacket

TPE mixture adapted to suit the requirements in e-chains®.



Overall shield

Extremely flexible braiding made of tinned copper wires. Coverage linear approx. 70%, optical approx. 90%



Outer jacket

Low-adhesion, halogen-free, highly abrasion-resistant PUR mixture, adapted to suit the requirements in e-chains® (according to DIN EN 50363-10-2).



Outer jacket colour

Pastel orange (comparable to RAL 2003)

CFRIP®

Strip cables faster: a tear strip is moulded into the inner jacket



Dynamic properties

	Min. bend radius, e-chain (factor)	7.5 x d
	Min. bend radius, e-chain	108.75 mm
	Min. bend radius, flexible (factor)	6 x d
	Min. bend radius, fixed (factor)	4 x d
	Temperature e-chain®	-25°C up to +80°C
	Temperature, flexible	-40°C to +80°C (according to DIN EN 60811-504)
	Temperature, fixed	-50°C to +80°C (according to DIN EN 50305)
	v max. unsupported (speed)	10 m/s
	v max. gliding (speed)	5 m/s
	a max. (acceleration)	80 m/s ²
	travel length	Class 5
	torsion	No torsion



chainflex®Lifetime

Guaranteed service life for this series according to guarantee conditions

Further information: [chainflex® guarantee](#)

Double strokes*	5 million	7.5 million	10 million
Temperature,	R min.	R min.	R min.
from/to [°C]	[Factor x d]	[Factor x d]	[Factor x d]
-25 /-15	10	11	12
-15 /+70	7.5	8.5	9.5
+70 / +80	10	11	12

* Higher number of double strokes possible - use the service life calculation function on this page.



Properties and approvals

	UV resistance	Medium
	Oil resistance	Oil-resistant (according to DIN EN 50363-10-2), Class 3
	Offshore	MUD-resistant according to NEK 606 - status 2018
	Flame-retardant	According to IEC 60332-1-2, Cable Flame, VW-1, FT1, FT2/Horizontal Flame
	Silicone-free	Free from silicone which can affect paint adhesion (according to PV 3.10.7 – status 1992)
	Halogen-free	According to DIN EN 60754
	UL verified	Certificate no. V293650: "igus 4-year chainflex cable guarantee and service life calculator based on 2 billion test cycles per year"
	UL/CSA AWM	Style 10492 and 20234, 1000 V, 80 °C
	NFPA	According to NFPA 79-2018, chapter 12.9
	DNV	Type approval certificate TAE00003XA
	REACH	In accordance with Regulation (EC) No. 1907/2006 (REACH)
	Lead-free	According to 2011/65/EU (RoHS-II/RoHS-III)
	Cleanroom	According to ISO Class 1. The outer jacket material of this series complies with CF77.UL.05.12.D - tested by IPA according to standard DIN EN ISO 14644-1
	DESINA	According to VDW, DESINA standardisation
	CE	According to 2014/35/EU



Certificates and standards

