

readycable® fan cable suitable for Lenze

EWLLxxxGMS, basic cable TPE 5xd

MAT9120031



readycable® fan cable suitable for Lenze

EWLLxxxGMS, basic cable TPE 5xd

- For heaviest duty applications
- TPE outer jacket
- Coolant-resistant
- Low-temperature-flexible
- Hydrolysis and microbe-resistant
- Halogen-free
- Silicone-free
- UV-resistant
- PVC-free
- Oil-resistant (following DIN EN 60811-404), resistant to bio oils (following VDMA 24568 with Plantocut 8 S-MB tested by DEA)
- CFRIP®
- Guarantee up to 4 years

Product description

Introducing the readycable® fan cable, designed for Lenze EWLLxxxGMS applications. This robust cable features a TPE outer jacket, making it suitable for the heaviest duty tasks. Its exceptional resistance to oil, including bio-oils, ensures durability in various environments. With low-temperature flexibility and UV resistance, it excels in both indoor and outdoor settings. Perfect for high-bay warehouses, machining units, and outdoor cranes, this cable is your reliable choice for demanding applications.

Manufacturer attributes

Manufacturer Part No	EWLLxxxGMS
Cable type	Basic cable

Connectors

Connector A	round plug, socket
Connector B	open cable end, cut off



General properties

Number of cores and conductor nominal cross-section	3G1.0
Outer diameter (d) max. mm	6 mm
Weight per km	54 kg/km
Copper index kg/km	30 kg/km

Electricity attributes

 Nominal voltage	300/500V
UL Voltage Rating	1000 V
 Test voltage	2000V (according to DIN EN 50395)
Maximum conductor resistance at 20°C [μm]	19.5000

Cable structure

 Conductor	Stranded conductor in an especially bend-resistant version consisting of bare copper wires (according to DIN EN 60228).
 Core insulation	Mechanically high-quality TPE mixture.
 Core stranding	Cores wound in a layer with short pitch length.
 Conductor colours	cores black with white numbers, one core green-yellow.
Core group 1 core structure	3G1.0
 Outer jacket	Low-adhesion, extremely abrasion-resistant and highly flexible TPE mixture, adapted to suit the requirements in e-chains®.
 Outer jacket colour	Steel blue (comparable to RAL 5011)
 CFRIP®	Strip cables faster: a tear strip is moulded into the outer jacket



Properties and approvals



UV resistance

High

Oil resistance

Oil-resistant (according to DIN EN 60811-404), bio-oil-resistant (according to VDMA 24568 with Plantocut 8 S-MB tested by DEA), Class 4



Silicone-free

Free from silicone which can affect paint adhesion (according to PV 3.10.7 – status 1992)

Halogen-free

According to DIN EN 60754



UL verified

Certificate no. V293650: "The igus 4-year chainflex cable guarantee and service life calculator based on 2 billion test cycles per year"

UL AWM

Style 11886 and 22351, 1000 V, 90 °C



REACH

In accordance with Regulation (EC) No. 1907/2006 (REACH)



Lead-free

According to 2011/65/EU (RoHS-II/RoHS-III)



Cleanroom

According to ISO Class 1, material/cable tested by IPA according to DIN EN ISO standard 14644-1



CE

According to 2014/35/EU



Dynamic properties

	Min. bend radius, e-chain (factor)	5 x d
	Min. bend radius, e-chain	30 mm
	Min. bend radius, flexible (factor)	4 x d
	Min. bend radius, fixed (factor)	3 x d
	Temperature e-chain®	-35°C up to +100°C
	Temperature, flexible	-50°C to +100°C (according to DIN EN 60811-504)
	Temperature, fixed	-55°C to +100°C (according to DIN EN 50305)
	v max. unsupported (speed)	10 m/s
	v max. gliding (speed)	6 m/s
	a max. (acceleration)	100 m/s ²
	travel length	Class 6
	torsion	Torsion ±90°, with 1m cable length, Class 2



chainflex®Lifetime

Guaranteed service life for this series according to guarantee conditions

Further information: [chainflex® guarantee](#)

Double strokes*	5 million	7.5 million	12.5 million
Temperature,	R min.	R min.	R min.
from/to [°C]	[Factor x d]	[Factor x d]	[Factor x d]
-35 / -25	6.8	7.5	8.5
-25 / +90	5	6	7
+90 / +100	6.8	7.5	8.5

* Higher number of double strokes possible - use the service life calculation function on this page.

Certificates and standards

