

readycable® servo cable suitable for Lenze

EYP0012AxxxxM02A00, basic cable PUR 7.5xd

MAT9120053



readycable® servo cable suitable for Lenze

EYP0012AxxxxM02A00, basic cable PUR 7.5xd

- For extremely heavy duty applications
- PUR outer jacket
- Shielded
- Oil-resistant and coolant-resistant
- Notch-resistant
- Flame retardant
- Hydrolysis and microbe-resistant
- Guarantee up to 4 years

Product description

Introducing the readycable® servo cable, designed specifically for Lenze EYP0012AxxxxM02A00 applications. This heavy-duty cable features a durable PUR outer jacket, offering exceptional resistance to oil, UV, and extreme temperatures. It's perfect for both indoor and outdoor use, ensuring reliability in storage units, machining tools, and cleanrooms. With its halogen-free, flame-retardant, and notch-resistant properties, this cable is built for long-lasting performance in demanding environments.

Manufacturer attributes

Manufacturer Part No	EYP0012AxxxxM02A00
Cable type	Basic cable

Connectors

Connector A	round plug, socket
Connector B	open cable end, cut off

General properties

Number of cores and conductor nominal cross-section	(4G2.5+(2x1.5)C)C
Outer diameter (d) max. mm	14.5 mm
Weight per km	306 kg/km
Copper index kg/km	199 kg/km



Electricity attributes

	Nominal voltage	600/1,000V (according to DIN VDE 0298-3)
	UL Voltage Rating	1000 V
	Test voltage	4000V (according to DIN EN 50395)

Cable structure

	Conductor	Stranded conductor in an especially bend-resistant version consisting of bare copper wires (according to DIN EN 60228).
	Core insulation	Mechanically high-quality, especially low-capacity XLPE mixture.
	Core stranding	Power cores with control pair elements wound with elements for high-tensile stresses.
	Conductor colours	Power cores: cores black with white digits, one core green-yellow. 1st core: U / L1 / C / L+ 2nd core: V / L2 3rd core: W / L3 / D / L- Control pair: Cores black with white numbers. 1st control wire: 4 2nd control wire: 5
	Core group 1 core structure	4G2.5
	Core group 2 core structure	(2x1.5)C)C
	Element shield	Extremely bend-resistant braiding made of tinned copper wires.
	Inner jacket	TPE mixture adapted to suit the requirements in e-chains®.
	Overall shield	Extremely flexible braiding made of tinned copper wires. Coverage linear approx. 70%, optical approx. 90%
	Outer jacket	Low-adhesion, halogen-free, highly abrasion-resistant PUR mixture, adapted to suit the requirements in e-chains® (according to DIN EN 50363-10-2).
	Outer jacket colour	Pastel orange (comparable to RAL 2003)
	CFRIP®	Strip cables faster: a tear strip is moulded into the inner jacket



Dynamic properties

	Min. bend radius, e-chain (factor)	7.5 x d
	Min. bend radius, e-chain	108.75 mm
	Min. bend radius, flexible (factor)	6 x d
	Min. bend radius, fixed (factor)	4 x d
	Temperature e-chain®	-25°C up to +80°C
	Temperature, flexible	-40°C to +80°C (according to DIN EN 60811-504)
	Temperature, fixed	-50°C to +80°C (according to DIN EN 50305)
	v max. unsupported (speed)	10 m/s
	v max. gliding (speed)	5 m/s
	a max. (acceleration)	80 m/s ²
	travel length	Class 5
	torsion	No torsion



chainflex®Lifetime

Guaranteed service life for this series according to guarantee conditions

Further information: [chainflex® guarantee](#)

Double strokes*	5 million	7.5 million	10 million
Temperature,	R min.	R min.	R min.
from/to [°C]	[Factor x d]	[Factor x d]	[Factor x d]
-25 /-15	10	11	12
-15 /+70	7.5	8.5	9.5
+70 / +80	10	11	12

* Higher number of double strokes possible - use the service life calculation function on this page.



Properties and approvals

	UV resistance	Medium
	Oil resistance	Oil-resistant (according to DIN EN 50363-10-2), Class 3
	Offshore	MUD-resistant according to NEK 606 - status 2018
	Flame-retardant	According to IEC 60332-1-2, Cable Flame, VW-1, FT1, FT2/Horizontal Flame
	Silicone-free	Free from silicone which can affect paint adhesion (according to PV 3.10.7 – status 1992)
	Halogen-free	According to DIN EN 60754
	UL verified	Certificate no. V293650: "igus 4-year chainflex cable guarantee and service life calculator based on 2 billion test cycles per year"
	UL/CSA AWM	Style 10492 and 20234, 1000 V, 80 °C
	NFPA	According to NFPA 79-2018, chapter 12.9
	DNV	Type approval certificate TAE00003XA
	REACH	In accordance with Regulation (EC) No. 1907/2006 (REACH)
	Lead-free	According to 2011/65/EU (RoHS-II/RoHS-III)
	Cleanroom	According to ISO Class 1. The outer jacket material of this series complies with CF77.UL.05.12.D - tested by IPA according to standard DIN EN ISO 14644-1
	DESINA	According to VDW, DESINA standardisation
	CE	According to 2014/35/EU



Certificates and standards

