


readycable® encoder cable suitable for NUM

AGOFRU030Mxxx (ext.), extension cable PVC 10xd

MAT9289011



readycable® encoder cable suitable for NUM

AGOFRU030Mxxx (ext.), extension cable PVC

10xd

- For medium-duty applications
- PVC outer jacket
- Oil resistant (following DIN EN 50363-4-1)
- Silicone-free
- Flame retardant
- Guarantee up to 4 years

Product description

Introducing the readycable encoder cable from the trusted brand, readycable. Designed for medium duty applications, this extension cable features a durable PVC outer jacket that is oil resistant and flame retardant. Ideal for both indoor and outdoor use in temperatures above 5°C, it supports unsupported travel distances and is perfect for storage and retrieval units, processing machines, and handling equipment. Elevate your performance with this reliable and versatile cable.

Manufacturer attributes

Manufacturer Part No	AGOFRU030Mxxx (ext.)
Cable type	Extension cable

Connectors

Connector A	Connector 23-pin socket solder
Connector B	Connector 23-pin pin solder

General properties

Drive technology system	Control Techniques, NUM, Siemens
Number of cores and conductor nominal cross-section	(3x(2x0.14)C)+(4x0.14)+(2x0.5))C
Outer diameter (d) max. mm	9 mm
Weight per km	100 kg/km
Copper index kg/km	64 kg/km




Electricity attributes

	Nominal voltage	50V
UL Voltage Rating		300 V
	Test voltage	500V

Cable structure

	Conductor	Very finely stranded special conductors of particularly bending resistant design made of tinned copper wires.
	Core insulation	Mechanically high-quality TPE mixture.
	Core stranding	According to measuring system specification
	Conductor colours	according to measuring system specification
Core group 1 core structure		3x(2x0.14)C
Core group 1 colour code		green/yellow, black/brown, red/orange
Core group 2 core structure		(4x0.14)
	Element shield	Extremely bend-resistant, tinned copper shielding. Cover approx. 90% optical
Element jacket		TPE mixture on pair shielding adapted to suit the requirements in e-chains®.
	Overall shield	Extremely bend-resistant braiding made of tinned copper wires. Coverage approx. 55% linear, approx. 80% optical
	Outer jacket	Low-adhesion, oil-resistant PVC mixture, adapted to suit the requirements in e-chains® (according to DIN EN 50363-4-1).
	Outer jacket colour	Yellow-green (comparable to RAL 6018)



- 1. Outer jacket: pressure extruded, oil-resistant PVC mixture
- 2. Overall shield: extremely flexible braiding made of tinned copper wires
- 3. Banding: plastic foil
- 4. Element jacket: mechanically high-quality TPE mixture
- 5. Element shield: extremely flexible tinned copper wire
- 6. Core insulation: mechanically high-quality TPE mixture
- 7. Conductor: very finely stranded special conductors of a particularly bend-resistant design, made of tinned copper wires.
- 8. Strain relief: high tensile strength centre element



Properties and approvals

	UV resistance	none
	Oil resistance	Oil-resistant (according to DIN EN 50363-4-1), Class 2
	Flame-retardant	According to IEC 60332-1-2, Cable Flame, VW-1, FT1, FT2/Horizontal Flame
	Silicone-free	Free from silicone which can affect paint adhesion (according to PV 3.10.7 – status 1992)
	UL verified	Certificate no. V293650: "The igus 4-year chainflex cable guarantee and service life calculator based on 2 billion test cycles per year"
	UL/CSA AWM	Style 10467 and 2464, 300 V, 80 °C
	NFPA	According to NFPA 79-2018, chapter 12.9
	REACH	In accordance with Regulation (EC) No. 1907/2006 (REACH)
	Lead-free	According to 2011/65/EU (RoHS-II/RoHS-III)
	Cleanroom	According to ISO Class 2. The outer jacket material of this series complies with CF5.10.07 - tested by IPA according to standard DIN EN ISO 14644-1
	CE	According to 2014/35/EU



Dynamic properties

	Min. bend radius, e-chain (factor)	10 x d
	Min. bend radius, e-chain	90 mm
	Min. bend radius, flexible (factor)	8 x d
	Min. bend radius, fixed (factor)	5 x d
	Temperature e-chain®	+5°C up to +70°C
	Temperature, flexible	-5°C to +70°C (according to DIN EN 60811-504)
	Temperature, fixed	-15°C to +70°C (according to DIN EN 50305)
	v max. unsupported (speed)	5 m/s
	v max. gliding (speed)	3 m/s
	a max. (acceleration)	30 m/s ²
	travel length	Class 2
	torsion	No torsion



chainflex®Lifetime

Guaranteed service life for this series according to guarantee conditions
Further information: [chainflex® guarantee](#)

Double strokes*					5 million	7.5 million	10 million
Temperature,	v max. [m/s]		a max.	Travel	R min. [Factor x d]	R min. [Factor x d]	R min. [Factor x d]
from/to [°C]	unsupported	gliding	[m/s²]	[m]			
+5/ +15					12.5	13.5	14.5
+15 / +60	5	3	30	≤ 10	10	11	12
+60 / +70					12.5	13.5	14.5

* Higher number of double strokes possible - please ask for your individual calculation.

Certificates and standards

