

readycable® signal cable suitable for Fanuc

LX660-4077-T319, basic cable PUR 10xd

MAT9300319



readycable® signal cable suitable for Fanuc

LX660-4077-T319, basic cable PUR 10xd

- For medium-duty applications
- PUR outer jacket
- Oil-resistant (according to DIN EN 50363-10-2)
- Halogen-free
- Silicone-free
- Flame retardant
- Offshore
- Coolant-resistant
- Hydrolysis and microbe-resistant
- Overall shield
- Notch-resistant
- PVC-free
- Guarantee up to 4 years

Product description

Introducing the readycable® signal cable, designed for Fanuc LX660-4077-T319 applications. This medium-duty cable features a durable PUR outer jacket that is oil-resistant, halogen-free, and silicone-free. Ideal for both indoor and outdoor use without direct sunlight, it offers excellent protection against coolants and microbes. With a flame-retardant design and notch resistance, this cable is perfect for processing and machine tools, ensuring reliable performance in low-temperature environments.

Manufacturer attributes

Manufacturer Part No	LX660-4077-T319
Cable type	Basic cable

Connectors

Connector A	round plug, socket
Connector B	rectangular connector, pin



General properties

Number of cores and conductor nominal cross-section	((4x0.25)+3x(2x0.25+2x0.5))C
Outer diameter (d) max. mm	9.5 mm
Weight per km	117 kg/km
Copper index kg/km	80 kg/km


Electricity attributes

	Nominal voltage	50V
UL Voltage Rating		300 V
	Test voltage	500V



Cable structure

	Conductor	Very finely stranded special conductors of particularly bending resistant design made of tinned copper wires.
	Core insulation	Mechanically high-quality TPE mixture.
	Core stranding	According to measuring system specification
	Conductor colours	according to measuring system specification
Core group 1 core structure		(4x0.25)
Core group 1 colour code		white/brown/grey/black
Core group 2 core structure		3x2x0.25
	Element shield	Extremely bend-resistant, tinned copper shielding. Cover approx. 90% optical
Element jacket		TPE mixture on pair shielding adapted to suit the requirements in e-chains®.
	Overall shield	Bend-resistant braiding made of tinned copper wires. Coverage approx. 55% linear, approx. 80% optical
	Outer jacket	Low-adhesion, halogen-free, highly abrasion-resistant PUR mixture, adapted to suit the requirements in e-chains® (according to DIN EN 50363-10-2).
	Outer jacket colour	Yellow-green (comparable to RAL 6018)

		1. Outer jacket: pressure extruded PUR mixture 2. Banding: plastic fleece 3. Overall shield: extremely flexible braiding made of tinned copper wires 4. Banding: plastic foil 5. Element shield: extremely flexible tinned copper wire 6. Element jacket: mechanically high-quality TPE mixture 7. Core insulation: mechanically high-quality TPE mixture 8. Conductor: very finely stranded special conductors of a particularly bend-resistant design, made of tinned copper wires. 9. Strain relief: high tensile strength centre element
---	--	--



Dynamic properties

	Min. bend radius, e-chain (factor)	10 x d
	Min. bend radius, e-chain	95 mm
	Min. bend radius, flexible (factor)	8 x d
	Min. bend radius, fixed (factor)	5 x d
	Temperature e-chain®	-25°C up to +80°C
	Temperature, flexible	-40°C to +80°C (according to DIN EN 60811-504)
	Temperature, fixed	-50°C to +80°C (according to DIN EN 50305)
	v max. unsupported (speed)	5 m/s
	v max. gliding (speed)	3 m/s
	a max. (acceleration)	30 m/s ²
	travel length	Class 2
	torsion	No torsion



chainflex®Lifetime

Guaranteed service life for this series according to guarantee conditions

Further information: [chainflex® guarantee](#)

Double strokes*	5 million	7.5 million	10 million
Temperature,	R min.	R min.	R min.
from/to [°C]	[Factor x d]	[Factor x d]	[Factor x d]
-25 / -15	12.5	13.5	14.5
-15 / +70	10	11	12
+70 / +80	12.5	13.5	14.5

* Higher number of double strokes possible - use the service life calculation function on this page.



Properties and approvals

	UV resistance	Medium
	Oil resistance	Oil-resistant (according to DIN EN 50363-10-2), Class 3
	Offshore	MUD-resistant according to NEK 606 - status 2018
	Flame-retardant	According to IEC 60332-1-2, Cable Flame, VW-1, FT1, FT2/Horizontal Flame
	Silicone-free	Free from silicone which can affect paint adhesion (according to PV 3.10.7 – status 1992)
	Halogen-free	According to DIN EN 60754
	UL verified	Certificate no. V293650: "The igus 4-year chainflex cable guarantee and service life calculator based on 2 billion test cycles per year"
	UL/CSA AWM	Style 10467 and 20233, 300 V, 80 °C
	NFPA	According to NFPA 79-2018, chapter 12.9
	DNV	Type approval certificate TAE00003X4
	REACH	In accordance with Regulation (EC) No. 1907/2006 (REACH)
	Lead-free	According to 2011/65/EU (RoHS-II/RoHS-III)
	Cleanroom	According to ISO Class 1. The outer jacket material of this series complies with CF77.UL.05.12.D - tested by IPA according to standard DIN EN ISO 14644-1
	DESINA	According to VDW, DESINA standardisation
	CE	According to 2014/35/EU



Certificates and standards

