

readycable® servo cable suitable for Kollmorgen /  
Danaher Motion 107492 (10m), basic cable, PVC  
7.5xd

MAT9340005



readycable® servo cable suitable for  
Kollmorgen / Danaher Motion 107492 (10m),  
basic cable, PVC 7.5xd

- For heavy-duty applications
- PVC outer jacket
- Oil resistant (following DIN EN 50363-4-1)
- Silicone-free
- Flame retardant
- Overall shield
- Guarantee up to 4 years

Product description

Introducing the readycable® servo cable, designed for heavy-duty applications and suitable for Kollmorgen / Danaher Motion 107492. This 10m cable features a durable PVC outer jacket that is both oil-resistant and flame-retardant, ensuring reliability in various environments. Ideal for indoor and outdoor use above 5°C, it supports unsupported and gliding travels up to 100m, making it perfect for storage and retrieval units, machining units, and indoor cranes. Experience robust performance with the readycable® series.

Manufacturer attributes

|                      |               |
|----------------------|---------------|
| Manufacturer Part No | 107492 (10 m) |
| Cable type           | Basic cable   |

Connectors

|             |                            |
|-------------|----------------------------|
| Connector A | Connector M23 socket 8-pin |
| Connector B | Circuit board connection   |

General properties

|                                                     |                   |
|-----------------------------------------------------|-------------------|
| Number of cores and conductor nominal cross-section | (4G1.5+(2x1.5)C)C |
| Outer diameter (d) max. mm                          | 13 mm             |
| Weight per km                                       | 256 kg/km         |
| Copper index kg/km                                  | 145 kg/km         |




Electricity attributes

|                                                                                  |                   |                                          |
|----------------------------------------------------------------------------------|-------------------|------------------------------------------|
|  | Nominal voltage   | 600/1,000V (according to DIN VDE 0298-3) |
|                                                                                  | UL Voltage Rating | 1000 V                                   |
|  | Test voltage      | 4000V (according to DIN EN 50395)        |



## Cable structure

|                                                                                    |                            |                                                                                                                                                                                                                               |
|------------------------------------------------------------------------------------|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|    | <b>Conductor</b>           | Stranded conductor in an especially bend-resistant version consisting of bare copper wires (according to DIN EN 60228).                                                                                                       |
|    | <b>Core insulation</b>     | Mechanically high-quality, especially low-capacity XLPE mixture.                                                                                                                                                              |
|    | <b>Core stranding</b>      | Power cores with control pair elements wound with elements for high-tensile stresses.                                                                                                                                         |
|    | <b>Conductor colours</b>   | Power cores: cores black with white digits, one core green-yellow. 1st core: U / L1 / C / L+ 2nd core: V / L2 3rd core: W / L3 / D / L- Control pair: Cores black with white numbers. 1st control wire: 4 2nd control wire: 5 |
| <b>Core group 1 core structure</b>                                                 |                            | 4G1.5                                                                                                                                                                                                                         |
| <b>Core group 2 core structure</b>                                                 |                            | (2x1.5)C)C                                                                                                                                                                                                                    |
|    | <b>Element shield</b>      | Extremely bend-resistant braiding made of tinned copper wires.                                                                                                                                                                |
| <b>Inner jacket</b>                                                                |                            | PVC mixture adapted to suit the requirements in e-chains®.                                                                                                                                                                    |
|    | <b>Overall shield</b>      | Extremely flexible braiding made of tinned copper wires. Coverage linear approx. 70%, optical approx. 90%                                                                                                                     |
|  | <b>Outer jacket</b>        | Low-adhesion PVC mixture, adapted to suit the requirements in e-chains® (according to DIN EN 50363-4-1).                                                                                                                      |
|  | <b>Outer jacket colour</b> | Moss green (comparable to RAL 6005)                                                                                                                                                                                           |
| <b>CFRIP®</b>                                                                      |                            | Strip cables faster: a tear strip is moulded into the inner jacket                                                                                                                                                            |



1. Outer jacket: pressure-extruded, oil-resistant PVC mixture
2. Overall shield: extremely flexible braiding made of tinned copper wires.
3. Inner jacket: pressure-extruded, gusset-filling PVC mixture
4. Core insulation: mechanically high-quality, especially low-capacitance TPE mixture
5. Conductor: particularly resistant to bending made of bare copper wires
6. Element banding: plastic foil
7. Element shield: extremely flexible tinned copper wire
8. Shield film: aluminium-coated plastic foil
9. Strain relief: high tensile strength centre element



## Properties and approvals

|                                                                                    |                        |                                                                                                                                                     |
|------------------------------------------------------------------------------------|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
|    | <b>UV resistance</b>   | Medium                                                                                                                                              |
|    | <b>Oil resistance</b>  | Oil-resistant (according to DIN EN 50363-4-1), Class 2                                                                                              |
|    | <b>Flame-retardant</b> | According to IEC 60332-1-2, Cable Flame, VW-1, FT1, FT2/Horizontal Flame                                                                            |
|    | <b>Silicone-free</b>   | Free from silicone which can affect paint adhesion (according to PV 3.10.7 – status 1992)                                                           |
|    | <b>UL verified</b>     | Certificate no. V293650: "The igus 4-year chainflex cable guarantee and service life calculator based on 2 billion test cycles per year"            |
|    | <b>UL/CSA AWM</b>      | Style 30052 und 20886, 1000V, 90°C                                                                                                                  |
|    | <b>NFPA</b>            | According to NFPA 79-2018, chapter 12.9                                                                                                             |
|   | <b>REACH</b>           | In accordance with Regulation (EC) No. 1907/2006 (REACH)                                                                                            |
|  | <b>Lead-free</b>       | According to 2011/65/EU (RoHS-II/RoHS-III)                                                                                                          |
|  | <b>Cleanroom</b>       | According to ISO Class 2. The outer jacket material of this series complies with CF5.10.07 - tested by IPA according to standard DIN EN ISO 14644-1 |
|  | <b>CE</b>              | According to 2014/35/EU                                                                                                                             |



## Dynamic properties

|                                                                                    |                                     |                                               |
|------------------------------------------------------------------------------------|-------------------------------------|-----------------------------------------------|
|    | Min. bend radius, e-chain (factor)  | 7.5 x d                                       |
|    | Min. bend radius, e-chain           | 97.5 mm                                       |
|    | Min. bend radius, flexible (factor) | 6 x d                                         |
|    | Min. bend radius, fixed (factor)    | 4 x d                                         |
|    | Temperature e-chain®                | +5°C up to +70°C                              |
|    | Temperature, flexible               | -5°C to +70°C (according to DIN EN 60811-504) |
|    | Temperature, fixed                  | -15°C to +70°C (according to DIN EN 50305)    |
|    | v max. unsupported (speed)          | 10 m/s                                        |
|   | v max. gliding (speed)              | 5 m/s                                         |
|  | a max. (acceleration)               | 80 m/s <sup>2</sup>                           |
|  | travel length                       | Class 5                                       |
|  | torsion                             | No torsion                                    |



chainflex®Lifetime

Guaranteed service life for this series according to guarantee conditions  
Further information: [chainflex® guarantee](#)

| Double strokes* | 5 million    | 7.5 million  | 10 million   |
|-----------------|--------------|--------------|--------------|
| Temperature,    | R min.       | R min.       | R min.       |
| from/to [°C]    | [Factor x d] | [Factor x d] | [Factor x d] |
| +5 / +15        | 10           | 11           | 12           |
| +15 / +60       | 7.5          | 8.5          | 9.5          |
| +60 / +70       | 10           | 11           | 12           |

\* Higher number of double strokes possible - use the service life calculation function on this page.

Certificates and standards

