

readycable® servo cable suitable for Kollmorgen /
Danaher Motion 90088 (5m), basic cable, PVC
7.5xd

MAT9340019



readycable® servo cable suitable for
Kollmorgen / Danaher Motion 90088 (5m),
basic cable, PVC 7.5xd

- For heavy-duty applications
- PVC outer jacket
- Oil resistant (following DIN EN 50363-4-1)
- Silicone-free
- Flame retardant
- Overall shield
- Guarantee up to 4 years

Product description

Introducing the readycable® servo cable, designed for heavy-duty applications. This 5m cable features a durable PVC outer jacket that is both oil resistant and flame retardant, ensuring reliable performance in various environments. Ideal for indoor and outdoor use above 5°C, it excels in unsupported and gliding travels up to 100m. Perfect for storage and retrieval units, machining units, and indoor cranes, this silicone-free cable is your go-to solution for demanding tasks.

Manufacturer attributes

Manufacturer Part No	90088 (5 m)
Cable type	Basic cable

Connectors

Connector A	round plug, socket
Connector B	SUB-D, pin

General properties

Number of cores and conductor nominal cross-section	(4G1.5+(2x1.5)C)C
Outer diameter (d) max. mm	13 mm
Weight per km	256 kg/km
Copper index kg/km	145 kg/km



Electricity attributes



Nominal voltage

600/1,000V (according to DIN VDE 0298-3)

UL Voltage Rating

1000 V



Test voltage

4000V (according to DIN EN 50395)

Properties and approvals



UV resistance

Medium



Oil resistance

Oil-resistant (according to DIN EN 50363-4-1), Class 2



Flame-retardant

According to IEC 60332-1-2, Cable Flame, VW-1, FT1, FT2/Horizontal Flame



Silicone-free

Free from silicone which can affect paint adhesion (according to PV 3.10.7 – status 1992)



UL verified

Certificate no. V293650: "The igus 4-year chainflex cable guarantee and service life calculator based on 2 billion test cycles per year"



UL/CSA AWM

Style 30052 und 20886, 1000V, 90°C



NFPA

According to NFPA 79-2018, chapter 12.9



REACH

In accordance with Regulation (EC) No. 1907/2006 (REACH)



Lead-free

According to 2011/65/EU (RoHS-II/RoHS-III)



Cleanroom

According to ISO Class 2. The outer jacket material of this series complies with CF5.10.07 - tested by IPA according to standard DIN EN ISO 14644-1




CE

According to 2014/35/EU



Cable structure

	Conductor	Stranded conductor in an especially bend-resistant version consisting of bare copper wires (according to DIN EN 60228).
	Core insulation	Mechanically high-quality, especially low-capacity XLPE mixture.
	Core stranding	Power cores with control pair elements wound with elements for high-tensile stresses.
	Conductor colours	Power cores: cores black with white digits, one core green-yellow. 1st core: U / L1 / C / L+ 2nd core: V / L2 3rd core: W / L3 / D / L- Control pair: Cores black with white numbers. 1st control wire: 4 2nd control wire: 5
Core group 1 core structure		4G1.5
Core group 2 core structure		(2x1.5)C)C
	Element shield	Extremely bend-resistant braiding made of tinned copper wires.
Inner jacket		PVC mixture adapted to suit the requirements in e-chains®.
	Overall shield	Extremely flexible braiding made of tinned copper wires. Coverage linear approx. 70%, optical approx. 90%
	Outer jacket	Low-adhesion PVC mixture, adapted to suit the requirements in e-chains® (according to DIN EN 50363-4-1).
	Outer jacket colour	Moss green (comparable to RAL 6005)
CFRIP®		Strip cables faster: a tear strip is moulded into the inner jacket



1. Outer jacket: pressure-extruded, oil-resistant PVC mixture
2. Overall shield: extremely flexible braiding made of tinned copper wires.
3. Inner jacket: pressure-extruded, gusset-filling PVC mixture
4. Core insulation: mechanically high-quality, especially low-capacitance TPE mixture
5. Conductor: particularly resistant to bending made of bare copper wires
6. Element banding: plastic foil
7. Element shield: extremely flexible tinned copper wire
8. Shield film: aluminium-coated plastic foil
9. Strain relief: high tensile strength centre element



Dynamic properties

	Min. bend radius, e-chain (factor)	7.5 x d
	Min. bend radius, e-chain	97.5 mm
	Min. bend radius, flexible (factor)	6 x d
	Min. bend radius, fixed (factor)	4 x d
	Temperature e-chain®	+5°C up to +70°C
	Temperature, flexible	-5°C to +70°C (according to DIN EN 60811-504)
	Temperature, fixed	-15°C to +70°C (according to DIN EN 50305)
	v max. unsupported (speed)	10 m/s
	v max. gliding (speed)	5 m/s
	a max. (acceleration)	80 m/s ²
	travel length	Class 5
	torsion	No torsion



chainflex®Lifetime

Guaranteed service life for this series according to guarantee conditions

Further information: [chainflex® guarantee](#)

Double strokes*	5 million	7.5 million	10 million
Temperature,	R min.	R min.	R min.
from/to [°C]	[Factor x d]	[Factor x d]	[Factor x d]
+5 / +15	10	11	12
+15 / +60	7.5	8.5	9.5
+60 / +70	10	11	12

* Higher number of double strokes possible - use the service life calculation function on this page.

Certificates and standards

