

readycable® motor cable suitable for Kollmorgen /  
Danaher Motion 107489 (25m), basic cable, PVC  
7.5xd

**MAT9340052**



**readycable® motor cable suitable for  
Kollmorgen / Danaher Motion 107489 (25m),  
basic cable, PVC 7.5xd**

- For heavy-duty applications
- PVC outer jacket
- Overall shield
- Flame retardant
- Silicone-free
- UV resistance: medium
- Oil resistant (following DIN EN 50363-4-1)
- CFRIP®
- Guarantee up to 4 years

**Product description**

Introducing the readycable® motor cable, designed for heavy-duty applications and compatible with Kollmorgen / Danaher Motion 107489. This 25m basic cable features a durable PVC outer jacket that is flame retardant and oil resistant, making it ideal for both indoor and outdoor use in temperatures above 5°C. With medium UV resistance and overall shielding, it's perfect for storage and retrieval units, machining, and quick handling. Trust the reliability of readycable® for your demanding projects.

**Manufacturer attributes**

|                      |               |
|----------------------|---------------|
| Manufacturer Part No | 107489 (25 m) |
| Cable type           | Basic cable   |

**Connectors**

|             |                            |
|-------------|----------------------------|
| Connector A | Connector M23 socket 8-pin |
| Connector B | Circuit board connection   |



General properties

|                                                     |           |
|-----------------------------------------------------|-----------|
| Number of cores and conductor nominal cross-section | (4G1.5)C  |
| Outer diameter (d) max. mm                          | 10 mm     |
| Weight per km                                       | 157 kg/km |
| Copper index kg/km                                  | 89 kg/km  |

Electricity attributes

|                                                                                                         |                                          |
|---------------------------------------------------------------------------------------------------------|------------------------------------------|
|  <b>Nominal voltage</b> | 600/1,000V (according to DIN VDE 0298-3) |
| <b>UL Voltage Rating</b>                                                                                | 1000 V                                   |
|  <b>Test voltage</b>    | 4000V (according to DIN EN 50395)        |
| <b>Maximum conductor resistance at 20°C [ <math>\mu\Omega</math>/km]</b>                                | 13.3000                                  |



## Cable structure



### Conductor

Stranded conductor in an especially bend-resistant version consisting of bare copper wires (according to DIN EN 60228).



### Core insulation

Mechanically high-quality, especially low-capacity XLPE mixture.



### Core stranding

Cores wound with a short pitch length around a high tensile strength centre element.



### Conductor colours

Cores black with white numbers, one core green-yellow. 1st core: U / L1 / C / L+ 2nd core: V / L2  
3rd core: W / L3 / D / L- 4th core: 4 / N  
(4G1.5)C

### Core group 1 core structure



### Inner jacket

PVC mixture adapted to suit the requirements in e-chains®.



### Overall shield

Extremely flexible braiding made of tinned copper wires. Coverage linear approx. 70%, optical approx. 90%



### Outer jacket

Low-adhesion, oil-resistant PVC mixture, adapted to suit the requirements in e-chains® (according to DIN EN 50363-4-1).




### Outer jacket colour

Jet black (comparable to RAL 9005)



### CFRIP®

Strip cables faster: a tear strip is moulded into the inner jacket



1. Outer jacket: pressure extruded, oil-resistant PVC mixture
2. Overall shield: extremely flexible braiding made of tinned copper wires
3. Inner jacket: pressure-extruded, gusset-filling PVC mixture
4. CFRIP: tear strip for faster stripping
5. Core insulation: mechanically high-quality, especially low-capacity XLPE mixture
6. Conductor: particularly flexible version consisting of bare copper wires
7. Strain relief: high tensile strength centre element



## Properties and approvals

|                                                                                    |                        |                                                                                                                                                     |
|------------------------------------------------------------------------------------|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
|    | <b>UV resistance</b>   | Medium                                                                                                                                              |
|    | <b>Oil resistance</b>  | Oil-resistant (according to DIN EN 50363-4-1), Class 2                                                                                              |
|    | <b>Flame-retardant</b> | According to IEC 60332-1-2, Cable Flame, VW-1, FT1, FT2/Horizontal Flame                                                                            |
|    | <b>Silicone-free</b>   | Free from silicone which can affect paint adhesion (according to PV 3.10.7 – status 1992)                                                           |
|    | <b>UL verified</b>     | Certificate no. V293650: "The igus 4-year chainflex cable guarantee and service life calculator based on 2 billion test cycles per year"            |
|    | <b>UL/CSA AWM</b>      | Style 30052 und 20886, 1000V, 90°C                                                                                                                  |
|    | <b>NFPA</b>            | According to NFPA 79-2018, chapter 12.9                                                                                                             |
|   | <b>REACH</b>           | In accordance with Regulation (EC) No. 1907/2006 (REACH)                                                                                            |
|  | <b>Lead-free</b>       | According to 2011/65/EU (RoHS-II/RoHS-III)                                                                                                          |
|  | <b>Cleanroom</b>       | According to ISO Class 2. The outer jacket material of this series complies with CF5.10.07 - tested by IPA according to standard DIN EN ISO 14644-1 |
|  | <b>CE</b>              | According to 2014/35/EU                                                                                                                             |



## Dynamic properties

|                                                                                    |                                     |                                               |
|------------------------------------------------------------------------------------|-------------------------------------|-----------------------------------------------|
|    | Min. bend radius, e-chain (factor)  | 7.5 x d                                       |
|    | Min. bend radius, e-chain           | 75 mm                                         |
|    | Min. bend radius, flexible (factor) | 6 x d                                         |
|    | Min. bend radius, fixed (factor)    | 4 x d                                         |
|    | Temperature e-chain®                | +5°C up to +70°C                              |
|    | Temperature, flexible               | -5°C to +70°C (according to DIN EN 60811-504) |
|    | Temperature, fixed                  | -15°C to +70°C (according to DIN EN 50305)    |
|    | v max. unsupported (speed)          | 10 m/s                                        |
|   | v max. gliding (speed)              | 5 m/s                                         |
|  | a max. (acceleration)               | 80 m/s <sup>2</sup>                           |
|  | travel length                       | Class 5                                       |
|  | torsion                             | No torsion                                    |



chainflex®Lifetime

Guaranteed service life for this series according to guarantee conditions

Further information: [chainflex® guarantee](#)

| Double strokes* | 5 million    | 7.5 million  | 10 million   |
|-----------------|--------------|--------------|--------------|
| Temperature,    | R min.       | R min.       | R min.       |
| from/to [°C]    | [Factor x d] | [Factor x d] | [Factor x d] |
| +5 / +15        | 10           | 11           | 12           |
| +15 / +60       | 7.5          | 8.5          | 9.5          |
| +60 / +70       | 10           | 11           | 12           |

\* Higher number of double strokes possible - use the service life calculation function on this page.

Certificates and standards

