

readycable® motor cable suitable for Allen Bradley

2090-CPWM4DF-14AFxx, basic cable PVC 15xd

MAT9461798



readycable® motor cable suitable for Allen

Bradley 2090-CPWM4DF-14AFxx, basic cable

PVC 15xd

- For flexing applications
- PVC outer jacket
- Overall shield
- Flame retardant
- Silicone-free
- Not oil-resistant
- Guarantee up to 4 years

Product description

Introducing the readycable® motor cable, designed for Allen Bradley 2090-CPWM4DF-14AFxx. This flexible cable features a durable PVC outer jacket and an overall shield, ensuring reliability in indoor applications. Ideal for unsupported travels up to 10m, it's perfect for wood and stone processing, packaging, and handling devices. With flame-retardant properties and silicone-free material, this cable is built for performance without the influence of oil. Upgrade your operations with this essential motor cable solution.

Manufacturer attributes

Manufacturer Part No	2090-CPWM4DF-14AFxx
Cable type	Basic cable

Connectors

Connector A	round plug, socket
Connector B	open cable end

General properties

Number of cores and conductor nominal cross-section	(4G2.5)C
Outer diameter (d) max. mm	10.5 mm
Weight per km	181 kg/km
Copper index kg/km	132 kg/km



Electricity attributes



Nominal voltage

600/1,000V (according to DIN VDE 0298-3)

UL Voltage Rating

1000 V



Test voltage

4000V (according to DIN EN 50395)

Properties and approvals



UV resistance

none



Oil resistance

No oil resistance



Flame-retardant

According to IEC 60332-1-2, Cable Flame, VW-1, FT1, FT2/Horizontal Flame



Silicone-free

Free from silicone which can affect paint adhesion (according to PV 3.10.7 – status 1992)



UL verified

Certificate no. V293650: "The igus 4-year chainflex cable guarantee and service life calculator based on 2 billion test cycles per year"



UL/CSA AWM

Style 10492 and 2570, 1000 V, 80 °C



NFPA

According to NFPA 79-2018, chapter 12.9



REACH

In accordance with Regulation (EC) No. 1907/2006 (REACH)



Lead-free

According to 2011/65/EU (RoHS-II/RoHS-III)




CE

According to 2014/35/EU



Cable structure

	Conductor	Conductor consisting of bare copper wires (according to DIN EN 60228).
	Core insulation	Mechanically high-quality, especially low-capacitance TPE mixture.
	Core stranding	Cores wound with an optimised pitch length.
	Conductor colours	cores black with white numbers, one core green-yellow. 1st core: U / L1 / C / L+ 2nd core: V / L2 3rd core: W / L3 / D / L- (4G2.5)C
Core group 1 core structure		
	Overall shield	Braiding made of tinned copper wires. Cover approx. 60% optical.
	Outer jacket	Low-adhesion PVC mixture, adapted to suit the requirements in e-chains®.
	Outer jacket colour	Pastel orange (comparable to RAL 2003)



1. Outer jacket: pressure-extruded PVC mixture
2. Overall shield: braiding made of tinned copper wires
3. Shield film: aluminium-coated plastic foil
4. Banding: plastic foil
5. Filler: plastic yarns
6. Core insulation: mechanically high-quality, especially low-capacity TPE mixture
7. Conductor: strands consisting of bare copper wires
8. Strain relief: plastic core element



Dynamic properties

	Min. bend radius, e-chain (factor)	15 x d
	Min. bend radius, e-chain	157.5 mm
	Min. bend radius, flexible (factor)	12 x d
	Min. bend radius, fixed (factor)	8 x d
	Temperature e-chain®	+5°C up to +70°C
	Temperature, flexible	-5°C to +70°C (according to DIN EN 60811-504)
	Temperature, fixed	-15°C to +70°C (according to DIN EN 50305)
	v max. unsupported (speed)	3 m/s
	v max. gliding (speed)	0 m/s
	a max. (acceleration)	20 m/s ²
	travel length	Class 1
	torsion	No torsion



chainflex®Lifetime

Guaranteed service life for this series according to guarantee conditions

Further information: [chainflex® guarantee](#)

Double strokes*	1 million	3 million	5 million
Temperature,	R min.	R min.	R min.
from/to [°C]	[Factor x d]	[Factor x d]	[Factor x d]
+5 / +15	17.5	18.5	19.5
+15 / +60	15	16	17
+60 / +70	17.5	18.5	19.5

* Higher number of double strokes possible - use the service life calculation function on this page.

Certificates and standards

