

readycable® servo cable suitable for Lenze

iEWMxxxGMS-040I, basic cable iguPUR 15xd

MAT9551130



readycable® servo cable suitable for Lenze

iEWMxxxGMS-040I, basic cable iguPUR 15xd

- For flexing applications
- iguPUR outer jacket
- Oil-resistant (according to DIN EN 50363-10-2)
- Silicone-free
- Flame retardant
- Overall shield
- Guarantee up to 4 years

Product description

Introducing the readycable® servo cable, designed specifically for Lenze iEWMxxxGMS-040I applications. This cable features a durable iguPUR outer jacket, making it suitable for flexing applications and resistant to oil, ensuring reliable performance indoors and outdoors. With a flame-retardant design and overall shielding, it is perfect for unsupported travels up to 10m and low-temperature scenarios. Trust in the quality and flexibility of readycable® for your processing and machine tool needs.

Manufacturer attributes

Manufacturer Part No	iEWMxxxGMS-040I
Cable type	Basic cable

Connectors

Connector A	round plug, socket
Connector B	open cable end, cut off

General properties

Number of cores and conductor nominal cross-section	(4G4.0+(2x1.5)C)C
Outer diameter (d) max. mm	14.5 mm
Weight per km	329 kg/km
Copper index kg/km	236 kg/km



Electricity attributes



Nominal voltage

600/1,000V (according to DIN VDE 0298-3)

UL Voltage Rating

1000 V



Test voltage

4000V (according to DIN EN 50395)

Cable structure



Conductor

Conductor consisting of bare copper wires (according to DIN EN 60228).



Core insulation

Mechanically high-quality, especially low-capacitance TPE mixture.



Core stranding

Power cores and control pair elements wound together in an optimised pitch length.



Conductor colours

Power cores: Cores black with white numbers, one core green-yellow. 1st core: U / L1 / C / L+ 2nd core: V / L2 3rd core: W / L3 / D / L- 1 control pair: Cores black with white numbers. 1st control wire: 5 2nd control wire: 6

Core group 1 core structure

4G4.0

Core group 2 core structure

(2x1.5)C)C



Element shield

Foil taping of optimised, flexible foil shield.



Overall shield

Braiding made of tinned copper wires. Cover approx. 60% optical.




Outer jacket

Low-adhesion iguPUR mixture, adapted to suit the requirements in e-chains®.



Outer jacket colour

Pastel orange (comparable to RAL 2003)



1. Outer jacket: pressure extruded iguPUR mixture
2. Overall shield: braiding made of tinned copper wires
3. Filler: plastic yarns
4. Core insulation: mechanically high-quality, especially low-capacitance TPE mixture
5. Conductor: strands consisting of bare copper wires
6. Shield film: aluminium-coated plastic foil
7. Banding: plastic foil
8. Element shield: tinned copper wires wrapped around it
9. Strain relief: plastic core element



Properties and approvals

	UV resistance	Medium
	Oil resistance	Oil-resistant (according to DIN EN 50363-10-2), Class 3
	Flame-retardant	According to IEC 60332-1-2, Cable Flame, VW-1, FT1, FT2/Horizontal Flame
	Silicone-free	Free from silicone which can affect paint adhesion (according to PV 3.10.7 – status 1992)
	UL verified	Certificate no. V293650: "The igus 4-year chainflex cable guarantee and service life calculator based on 2 billion test cycles per year"
	UL/CSA AWM	Style 10492 and 20940, 1000 V, 80 °C
	NFPA	According to NFPA 79-2018, chapter 12.9
	REACH	In accordance with Regulation (EC) No. 1907/2006 (REACH)
	Lead-free	According to 2011/65/EU (RoHS-II/RoHS-III)
	CE	According to 2014/35/EU



Dynamic properties

	Min. bend radius, e-chain (factor)	15 x d
	Min. bend radius, e-chain	217.5 mm
	Min. bend radius, flexible (factor)	12 x d
	Min. bend radius, fixed (factor)	8 x d
	Temperature e-chain®	-20°C up to +80°C
	Temperature, flexible	-40°C to +80°C (according to DIN EN 60811-504)
	Temperature, fixed	-50°C to +80°C (according to DIN EN 50305)
	v max. unsupported (speed)	3 m/s
	v max. gliding (speed)	0 m/s
	a max. (acceleration)	20 m/s ²
	travel length	Class 7
	torsion	No torsion



chainflex®Lifetime

Guaranteed service life for this series according to guarantee conditions

Further information: [chainflex® guarantee](#)

Double strokes*	1 million	3 million	5 million
Temperature,	R min.	R min.	R min.
from/to [°C]	[Factor x d]	[Factor x d]	[Factor x d]
-20 / -10	17.5	18.5	19.5
-10 / +70	15	16	17
+70 / +80	17.5	18.5	19.5

* Higher number of double strokes possible - use the service life calculation function on this page.

Certificates and standards

