

readycable® resolver cable suitable for Jetter cable

no. 723, basic cable, PVC 7.5xd

MAT9741810



readycable® resolver cable suitable for Jetter

cable no. 723, basic cable, PVC 7.5xd

- For heavy-duty applications
- PVC outer jacket
- Oil resistant (following DIN EN 50363-4-1)
- Flame retardant
- Silicone-free
- Guarantee up to 4 years

Product description

Introducing the readycable® resolver cable, designed for heavy-duty applications. This cable features a durable PVC outer jacket that is both oil-resistant and flame-retardant, ensuring reliable performance in various environments. Suitable for indoor and outdoor use at temperatures above 5°C, it supports unsupported travel distances and gliding applications up to 100m. Ideal for storage and retrieval units, machining units, and indoor cranes, this silicone-free cable is your go-to solution for robust connectivity.

Manufacturer attributes

Manufacturer Part No	723
Cable type	Connecting cable

Connectors

Connector A	SUB-D, pin
Connector B	round plug, socket

General properties

Number of cores and conductor nominal cross-section	(5x(2x0.25))C
Outer diameter (d) max. mm	8.5 mm
Weight per km	92 kg/km
Copper index kg/km	52 kg/km




Electricity attributes

	Nominal voltage	300/300V (according to DIN VDE 0298-3)
	UL Voltage Rating	300 V
	Test voltage	1500V (according to DIN EN 50395)
	Maximum conductor resistance at 20°C [Ω /km]	79.0000

Cable structure

	Conductor	Very finely stranded special conductors of a particularly bend-resistant design, made of bare copper wires.
	Core insulation	Mechanically high-quality TPE mixture.
	Core stranding	Cores twisted in pairs with short pitch lengths, core pairs then wound with short pitch lengths.
	Conductor colours	Colour code according to DIN 47100
	Overall shield	Extremely flexible braiding made of tinned copper wires. Coverage linear approx. 70%, optical approx. 90%
	Outer jacket	Low-adhesion, oil-resistant PVC mixture, adapted to suit the requirements in e-chains® (according to DIN EN 50363-4-1).
	Outer jacket colour	Silver grey (comparable to RAL 7001)



1. Outer jacket: pressure extruded, oil-resistant PVC mixture
2. Overall shield: extremely flexible braiding made of tinned copper wires.
3. Banding: plastic foil
4. Conductor: very finely stranded special conductor of particularly bend-resistant design made of bare copper wires
5. Core insulation: mechanically high-quality TPE mixture
6. Strain relief: high tensile strength centre element



Dynamic properties

	Min. bend radius, e-chain (factor)	7.5 x d
	Min. bend radius, e-chain	63.75 mm
	Min. bend radius, flexible (factor)	6 x d
	Min. bend radius, fixed (factor)	4 x d
	Temperature e-chain®	+5°C up to +70°C
	Temperature, flexible	-5°C to +70°C (according to DIN EN 60811-504)
	Temperature, fixed	-15°C to +70°C (according to DIN EN 50305)
	v max. unsupported (speed)	5 m/s
	v max. gliding (speed)	3 m/s
	a max. (acceleration)	50 m/s ²
	travel length	Class 5
	torsion	No torsion



chainflex® Lifetime

Guaranteed service life for this series according to the guarantee conditions

More information: chainflex® guarantee

Double strokes* 5 million 7.5 million 10 million

Temperatur, R min. R min. R min.

from/to [°C] [factor x d] [factor x d] [factor x d]

-25 / -15 10 11 12

-15 / +70 7.5 8.5 9.5

+70 / +80 10 11 12

* Higher number of double strokes possible - use the service life calculation function on this page.

Properties and approvals



UV resistance

Medium



Oil resistance

Oil-resistant (according to DIN EN 50363-4-1), Class 2



Flame-retardant

According to IEC 60332-1-2, Cable Flame, VW-1, FT1, FT2/Horizontal Flame



Silicone-free

Free from silicone which can affect paint adhesion (according to PV 3.10.7 – status 1992)



UL verified

Certificate no. V293650: "The igus 4-year chainflex cable guarantee and service life calculator based on 2 billion test cycles per year"

UL/CSA AWM

Style 10493 and 2464, 300 V, 80 °C



NFPA

According to NFPA 79-2018, chapter 12.9



REACH

In accordance with Regulation (EC) No. 1907/2006 (REACH)



Lead-free

According to 2011/65/EU (RoHS-II/RoHS-III)



Cleanroom

According to ISO Class 1. The outer jacket material of this series complies with CF240.02.24 - tested by IPA according to standard DIN EN ISO 14644-1



CE

According to 2014/35/EU

Certificates and standards

