

readycable® motor cable suitable for Allen Bradley

2090-CPWM7E7-08AF, extension cable PUR 10xd

MAT9861716



readycable® motor cable suitable for Allen

Bradley 2090-CPWM7E7-08AF, extension cable

PUR 10xd

- For medium-duty applications
- PUR outer jacket
- Shielded
- Oil-resistant and coolant-resistant
- Notch-resistant
- Flame retardant
- Hydrolysis and microbe-resistant
- PVC and halogen-free
- Guarantee up to 4 years

Product description

Introducing the readycable® motor cable, designed specifically for the Allen Bradley 2090-CPWM7E7-08AF. This extension cable features a durable PUR outer jacket, making it suitable for medium duty applications both indoors and outdoors. With exceptional oil, coolant, and hydrolysis resistance, plus flame retardant properties, it ensures reliable performance in challenging environments. Its halogen-free and PVC-free construction adds to its safety and sustainability credentials. Perfect for processing and machine tools, this cable is your go-to solution for demanding tasks.

Manufacturer attributes

Manufacturer Part No	2090-CPWM7E7-08AF
Cable type	Extension cable

Connectors

Connector A	round plug, socket
Connector B	coupling, pin



General properties

Drive technology system	Allen Bradley/Rockwell, Fanuc, SEW, Siemens
Number of cores and conductor nominal cross-section	(4G10)C
Outer diameter (d) max. mm	17 mm
Weight per km	551 kg/km
Copper index kg/km	495 kg/km

Electricity attributes

 Nominal voltage	600/1,000V (according to DIN VDE 0298-3)
UL Voltage Rating	1000 V
 Test voltage	4000V (according to DIN EN 50395)

Cable structure

 Conductor	Stranded conductor in an especially bend-resistant version consisting of bare copper wires (according to DIN EN 60228).
 Core insulation	Mechanically high-quality, especially low-capacity XLPE mixture.
 Core stranding	Cores wound with high tensile strength centre elements.
 Conductor colours	cores black with white numbers, one core green-yellow. 1st core: U / L1 / C / L+ 2nd core: V / L2 3rd core: W / L3 / D / L-
Core group 1 core structure	(4G10)C
 Overall shield	Bend-resistant braiding made of tinned copper wires. Coverage approx. 55% linear, approx. 80% optical
 Outer jacket	Low-adhesion, halogen-free, highly abrasion-resistant PUR mixture, adapted to suit the requirements in e-chains® (according to DIN EN 50363-10-2).
 Outer jacket colour	Pastel orange (comparable to RAL 2003)



Properties and approvals

	UV resistance	Medium
	Oil resistance	Oil-resistant (according to DIN EN 50363-10-2), Class 3
	Offshore	MUD-resistant according to NEK 606 - status 2018
	Flame-retardant	According to IEC 60332-1-2, Cable Flame, VW-1, FT1, FT2/Horizontal Flame
	Silicone-free	Free from silicone which can affect paint adhesion (according to PV 3.10.7 – status 1992)
	Halogen-free	According to DIN EN 60754
	UL verified	Certificate no. V293650: "igus 4-year chainflex cable guarantee and service life calculator based on 2 billion test cycles per year"
	UL/CSA AWM	Style 30052 und 21209, 1000 V, 90°C
	NFPA	According to NFPA 79-2018, chapter 12.9
	REACH	In accordance with Regulation (EC) No. 1907/2006 (REACH)
	Lead-free	According to 2011/65/EU (RoHS-II/RoHS-III)
	CE	According to 2014/35/EU



Dynamic properties

	Min. bend radius, e-chain (factor)	10 x d
	Min. bend radius, e-chain	170 mm
	Min. bend radius, flexible (factor)	8 x d
	Min. bend radius, fixed (factor)	5 x d
	Temperature e-chain®	-25°C up to +80°C
	Temperature, flexible	-40°C to +80°C (according to DIN EN 60811-504)
	Temperature, fixed	-50°C to +80°C (according to DIN EN 50305)
	v max. unsupported (speed)	10 m/s
	v max. gliding (speed)	2 m/s
	a max. (acceleration)	50 m/s ²
	travel length	Class 2
	torsion	No torsion



chainflex®Lifetime

Guaranteed service life for this series according to guarantee conditions
Further information: [chainflex® guarantee](#)

Double strokes*	5 million	7.5 million	10 million
Temperature,	R min.	R min.	R min.
from/to [°C]	[Factor x d]	[Factor x d]	[Factor x d]
-25 /-10	12.5	13.5	14.5
-15 /+70	10	11	12
+70 / +80	12.5	13.5	14.5

* Higher number of double strokes possible - use the service life calculation function on this page.

Certificates and standards

