

Guide rails and carriages – size 17



Complete Set



Order key
complete system ► Page 946

Type	Size	Options
NW - 22 - 17 - 30 - LLY		
drylin® N Guide carriages	Type of carriage	Type of carriage: 02: Carriage with threaded pin 22: Double carriage with threaded pin Options: P: Preload Floating bearing: LLY: Floating y-direction LLZ: Floating z-direction LLYZ: Floating yz-direction
	Rail width	
	Carriage length	
	Floating bearing in y-direction	

Guide rail – dimensions [mm]

Part No.	L	a	C4	C5: C6		h	h1	K1 ⁷³⁾	ly	lz	Weight
	max.			Min.	max.				[mm ⁴]	[mm ⁴]	[g/m]
NS-01-17- ⁷²⁾	2,000	17	60	20	49.5	5.5	0.9	Ø3.5	1,700	120	150
NS-01-17-UNGEBOHRT- ⁷²⁾	2,000	17	–	–	–	5.5	0.9	–	1,700	120	150
NS-01-17-AR- ⁷²⁾	2,000	17	60	20	49.5	5.5	0.9	Ø3.5	1,700	120	150

Guide carriage – dimensions [mm]

Part No.	H ±0.35	A	C	C2	K3 ⁷⁴⁾	Sp	Dp	Weight [g]
NW-02-17	6.0	9.6	20	14	M3	2.5	5.0	1.7
NW-02-17-P	6.0	9.6	20	14	M3	2.5	5.0	1.7
NW-22-17-30	6.0	9.6	30	18	M3	2.5	5.0	2.4
NW-22-17-40	6.0	9.6	40	28	M3	2.5	5.0	2.6

⁷²⁾ Please give the desired length in mm, hole pitches symmetrical C5=C6

⁷³⁾ For cap screw with low head (i.e. DIN 7984, DIN 6912, DIN 84, EN ISO 1707)

⁷⁴⁾ Metal thread



All elements can be ordered individually or as assembled systems

NS-01-17-1500: Guide rail, size 17, length 1,500 mm

NW-02-17-P-LLY: Guide carriage with threaded pin, size 17, pre-load, floating bearing in y-direction

NK-02-17-02-500-LLY: Complete system with two solid plastic guide carriages with threaded pins, size 17, floating bearing in y-direction and 500 mm guide rails with standard holes