



drylin® N guide carriage installation size 40  
iglidur® J sliding element  
**NW-01-40**



drylin® N guide carriage installation size 40  
iglidur® J sliding element

- Material sliding element: iglide® J
- Mounting type: Through holes
- Installation size: 40
- Load capacity, stat.: 157 lbs (700 N))

Product description

Introducing the drylin N guide carriage with installation size 40, featuring the innovative iglidur J sliding element. This reliable carriage is designed for easy mounting through holes, ensuring a secure fit. With a static load capacity of 157 lbs (700 N), it offers robust performance for various applications. Experience smooth operation and durability with this essential component from the drylin series, perfect for enhancing your projects.

Manufacturing and installation tolerances

|             |          |
|-------------|----------|
| H-tolerance | ±0,35 mm |
|-------------|----------|

Mechanical properties

|                      |       |
|----------------------|-------|
| Static load capacity | 700 N |
|----------------------|-------|

Dimensions

|     |        |
|-----|--------|
| A   | 23 mm  |
| C   | 50 mm  |
| C1  | 40 mm  |
| C2  | 20 mm  |
| H2  | 1.3 mm |
| Ø K | 4.5 mm |



General properties

|                          |               |
|--------------------------|---------------|
| Sliding element material | iglidur® J    |
| Floating bearing         | none          |
| Type of fastening        | Through holes |
| High temperature         | No            |