


iglidur® slewing ring, PRT-04, locking function with remote release

PRT-04-20-ART-RC



iglidur® slewing ring, PRT-04, locking function with remote release

- Remote release with adjustable Bowden cable in 5m length
- Easy release by hand
- Defined location points every 90°
- Compact, lightweight design
- Part of the PRT-04 series modular construction kit

Product description

Introducing the iglidur® PRT-04 slewing ring, designed for lubrication-free, dry operation. This innovative bearing features maintenance-free sliding elements made from tribologically optimized iglidur® materials and lightweight, hard anodized aluminum rings. The PRT-04 includes a remote release system with a 5-meter adjustable Bowden cable, ensuring easy operation even in hard-to-reach spaces. Enjoy precise adjustments under high loads with defined location points every 90°. Experience compact and ergonomic design with the PRT-04 series.

Thermal properties

Max. long-term application temperature	90 °C
Lower application temperature	-50 °C

General properties

Housing material	aluminium
------------------	-----------

Mechanical properties

Axial load, static	5000 N
Axial load, dynamic	1500 N
Radial load, dynamic	300 N
Rotating speed dry running [rpm]	300
max. permissible tilt moment	30 Nm



Dimensions

H	28 mm
D	80 mm
D1	70 mm
d1	30 mm
d	20 mm
Ø d2	60 mm
h	18 mm
T1	8 x 45 °
T2	8 x 45 °
S1	M4
S2	Ø4,5
K1	Ø4.5