



dryspin lead screw nut out of iglide R | geometry:
flange with spanner flat | metric thread | RH

RFRM-090913M5



dryspin lead screw nut out of iglide R |
geometry: flange with spanner flat | metric
thread | RH

- Material: iglide® R
- Thread direction: Right-hand thread
- Thread type: metric thread
- Design: Standard
- Cylindrical lead screw nut with flange

Product description

Introducing the drylin® flange lead screw nut with spanner flat from igus. Made from high-performance iglidur® R polymer, this lead screw nut is designed for medium to high speeds, providing excellent vibration dampening for a quieter operation. Its high wear resistance ensures durability under low loads, while it operates effectively in temperatures up to +90°C. This metric thread nut combines reliability and performance, making it an ideal choice for various applications.

Requirements

Mould-resistant according to DIN EN ISO 846 Procedure A	No
---	----

Thermal properties

Efficiency [η]	14-20
----------------	-------

General properties

Thread direction	Right-hand thread
Thread type	Metric thread; standard for highest compatibility
With spanner flat	Yes
Weight	27.625 g



Dimensions

Thread size	M5
Ø d1	5 mm
Ø d2	9 mm
Ø d3	18 mm
Ø d4	15.2 mm
Ø d5	3.2 mm
b1	13 mm
b2	3 mm