


drylin® T guide carriage TW-01  
TW-01-15



drylin® T guide carriage TW-01

- drylin® T linear carriage of the standard 01 series
- With individual clearance adjustment
- Long service life due to iglidur® J
- Optionally configurable as floating bearing version in y or z direction
- Material: aluminium housing, plastic lid, iglidur® J slider

Product description

Introducing the drylin T guide carriage TW-01, a reliable choice for your linear motion needs. This standard carriage features individual clearance adjustment for precise control and boasts a long service life thanks to its durable iglidur J material. With an aluminium housing and a plastic lid, it combines strength and lightweight design. Additionally, it can be configured as a floating bearing version in the y or z direction, making it versatile for various applications. Upgrade your projects with the drylin T carriage TW-01 today!

Manufacturing and installation tolerances

|             |          |
|-------------|----------|
| H-tolerance | ±0,35 mm |
|-------------|----------|

Mechanical properties

|                          |        |
|--------------------------|--------|
| Static load capacity Coy | 4000 N |
|--------------------------|--------|



Dimensions

|           |       |
|-----------|-------|
| H         | 24 mm |
| A         | 47 mm |
| C         | 74 mm |
| A1        | 16 mm |
| A2        | 38 mm |
| C1        | 50 mm |
| C2        | 30 mm |
| C3        | 9 mm  |
| H1        | 4 mm  |
| H5        | 16 mm |
| Thread K2 | M5    |
| Thread K3 | M4    |

General properties

|                          |            |
|--------------------------|------------|
| Sliding element material | iglidur® J |
| size                     | 01-15      |
| Floating bearing         | none       |

Certificates and standards

