


drylin® T guide carriage TW-03
TW-03-25



drylin® T guide carriage TW-03

- Please note: only runs on TS-01-20 rail
- drylin® T linear carriage from the 03 compact series
- Tall slim design
- For robust requirements
- Easy installation
- Captive sliding elements
- Preset bearing clearance
- Material: aluminium housing, stainless steel cover, iglidur® J2 slider
- Available as fixed and floating bearing (y- and z-direction)

Product description

Introducing the drylin® T guide carriage TW-03, a compact solution designed for robust industrial applications. With its tall slim design and easy installation, this carriage features loss-proof sliding elements for reliable operation. Crafted from high-quality aluminum and stainless steel, it offers both fixed and floating bearing options for flexible adaptation. Ideal for smooth and safe guidance of moving components, the TW-03 is perfect for those seeking durability and precision in their projects.

Manufacturing and installation tolerances

H-tolerance	±0,35 mm
-------------	----------

Mechanical properties

Static load capacity Coy	10000 N
--------------------------	---------



Dimensions

H	36 mm
A	48 mm
C	81 mm
A1	14 mm
A2	35 mm
C1	67.4 mm
C2	35 mm
H1	5 mm
H5	13 mm
Thread K2	M6

General properties

Sliding element material	iglidur® J
size	25
Floating bearing	none

Certificates and standards

