


drylin W complete carriage WWE-SL

WWE-10-40-10-SL



drylin W complete carriage WWE-SL

- Design: round
- Material sliding element: iglidur J
- Camera carriage 3/8" threaded hole
- Material: Die-cast zinc

Thread K2	M6
C	100 mm
A	73 mm
C2	87 mm
A2	60 mm

Product description

Introducing the drylin W complete carriage WWE-SL from igus. This round design features a durable sliding element made from iglidur J, ensuring smooth operation. Crafted from robust die-cast zinc, it includes a convenient 3/8" threaded hole for easy camera mounting. Ideal for various applications, this carriage combines reliability with strength, making it a perfect choice for your needs. Upgrade your setup with the drylin W complete carriage today!

Manufacturing and installation tolerances

H2-Tolerance	±0,25 mm
--------------	----------

Mechanical properties

Static load capacity Coy	4800 N
Static load capacity Coz	2400 N
Static load capacity Mox	96 Nm
Static load capacity Moy	170 Nm
Static load capacity Moz	170 Nm

Dimensions

A	73 mm
C	100 mm
A2	60 mm
C2	87 mm
Thread K2	M6
H2	24 mm



General properties

size	10-40
Design	round
Sliding element material	iglidur® J

Certificates and standards

