

drylin® R liner XUI-01

XUI-01-12



drylin® R liner XUI-01

- Material: iglidur® X
- Version: Long, enclosed type, high temperature
- Resistant to temperature and chemicals on stainless steel and chromed shafts

Product description

Introducing the drylin R liner XUI-01 from the trusted brand, igus. This long, enclosed liner is crafted from high-quality iglidur X material, ensuring exceptional resistance to high temperatures and chemicals. Designed for use on stainless steel and chromed shafts, it offers durability and reliability for your applications. Upgrade your machinery with this robust and efficient solution that stands the test of time.

Requirements

Mould-resistant according to DIN EN ISO 846 Procedure A	Yes
---	-----

Physical properties

Max. long-term application temperature	250 °C
Lower application temperature	-100 °C

Manufacturing and installation tolerances

d1 tolerance	+0.0016 +0.0024inch
di tolerance	H7
B tolerance	h10
r1 tolerance	+0.002 inch
t1 tolerance	+0.004 inch
f1 tolerance	+0.002 inch



Dimensions

Ø d1	0.75 mm
b1	1.575 in
r	0.1875 in
t	0.0391 in
Ø z	0.1339 in
Ø di	0.8747 in
B	1.625 in
t1	0.031 in
Ø Z1	0.142 in

Certificates and standards

